





3006120019

34090

34090 ZB4CS-4-12-N 4-Way Splitter

- high power, up to 12W input power
- ✓ wideband, 100 to 440 MHz
- low insertion loss, 0.6 dB typ.
- high isolation, 27 dB typ.

Description

High power splitter for 4 antennas

Specifications

GENERAL

Manufacturer:Mini-CircuitsDimensions (WXHXD)115 x 90 x 45 mmFreq. range200-500 MHzIsolation (typical / min.)31 dB / 20 dBInsertion loss (above theoretical, {4 way = 6 dB} typ. /max.)0.3 dB / 1.0 dBPhase unbalance (typical / max.)0.3 deg. / 3.0 degAmplitude unbalance (typical / max.):0.1 dB / 0.4 dBPower input15 WConnectorN-female for use, N-male on cableRecommended cableLow loss type coaxial 500hm. Max lenght from transmitter U952T to antenna is 50 m		
Freq. range 200-500 MHz Isolation (typical / min.) 31 dB / 20 dB Insertion loss (above theoretical, {4 way = 6 dB} typ. /max.) Phase unbalance (typical / max.): Amplitude unbalance (typical / max.): Power input 15 W Connector N-female for use, N-male on cable Low loss type coaxial 500hm. Max lenght from transmitter U952T to	Manufacturer:	Mini-Circuits
Isolation (typical / min.) 31 dB / 20 dB Insertion loss (above theoretical, {4 way = 6 dB} typ. /max.) 0.3 dB / 1.0 dB Phase unbalance (typical / max.) 0.3 deg. / 3.0 deg Amplitude unbalance (typical / max.): 0.1 dB / 0.4 dB Power input 15 W Connector N-female for use, N-male on cable Low loss type coaxial 50ohm. Max lenght from transmitter U952T to	Dimensions (WXHXD)	115 x 90 x 45 mm
Insertion loss (above theoretical, {4 way = 6 dB} typ. /max.) Phase unbalance (typical / max.) Amplitude unbalance (typical / max.): Power input 15 W Connector N-female for use, N-male on cable Low loss type coaxial 50ohm. Max length from transmitter U952T to	Freq. range	200-500 MHz
theoretical, {4 way = 6 dB} typ. /max.) Phase unbalance (typical / max.) Amplitude unbalance (typical / max.): Power input 15 W Connector N-female for use, N-male on cable Low loss type coaxial 500hm. Max lenght from transmitter U952T to	Isolation (typical / min.)	31 dB / 20 dB
(typical / max.) Amplitude unbalance (typical / max.): Power input 15 W Connector N-female for use, N-male on cable Low loss type coaxial 500hm. Max lenght from transmitter U952T to	theoretical, {4 way = 6	0.3 dB / 1.0 dB
(typical / max.): Power input 15 W Connector N-female for use, N-male on cable Low loss type coaxial 500hm. Max lenght from transmitter U952T to		0.3 deg. / 3.0 deg
Connector N-female for use, N-male on cable Low loss type coaxial 500hm. Max lenght from transmitter U952T to	-	0.1 dB / 0.4 dB
Connector male on cable Low loss type coaxial 50ohm. Max lenght from transmitter U952T to	Power input	15 W
Recommended cable 50ohm. Max lenght from transmitter U952T to	Connector	
	Recommended cable	50ohm. Max lenght from transmitter U952T to

Used With



CXL-70 34260

Antenna Unit Antenna 410–470 MHZ K702021 Unit