

# <sup>2220012101</sup> C1000-48T-4G-L

Cisco C1000 48port 1G switch with 4x1G SFP





## Description

Cisco Catalyst 1000 Series Switches are fixed managed Gigabit Ethernet and Fast Ethernet enterprise-class Layer 2 switches designed for small businesses and branch offices. These are simple, flexible and secure switches ideal for out-of-the-wiring-closet and critical Internet of Things (IoT) deployments. Cisco Catalyst 1000 operate on Cisco IOS Software and support simple device management and network management via a Command-Line Interface (CLI) as well as an on-box web UI. These switches deliver enhanced network security, network reliability, and operational efficiency for small organizations.

#### www.zenitel.com

#### info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

## Specifications

Cisco Catalyst 1000-48T-4G-L is managed 48-port switch with 48 auto-sensing 10/100/1000 ports and 4x Gigabit Ethernet SFP ports .

### PORTS

10/100/1000 RJ45	48
SFP	4
Console ports	1x RJ45, USB mini-B and USB-A (for storage and Bluetooth console)

### **ENVIRONMENT**

Operating temperature	-5°to 50°C
Operating relative	5% to 90% at 40°C
humidity	(non-condensing)

## **ELECTRICAL CHARACTERISTICS**

Frequency	50 to 60 Hz
AC voltage	110 to 220 VAC
Current	0.74A to 1.29A
Maximum power Consumption	53.66W
Maximum Power Wattage for BTU/hr	64.83

## **DIMENSIONS & WEIGHT**

Dimensions (W x D x H)	444 x 288 x 44 mm
Weight	3.95 kg
Mounting	Rack Mountable, 1HU

#### www.zenitel.com

#### info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.