

2220012164

GLC-TE

Cisco GLC-TE 1000BASE-T 1G SFP Transceiver - RJ45



Description

The 1000BASE-T SFP operates on standard Category 5 unshielded twisted pair copper cabling of up to 100m (328 ft) link length. Cisco 1000BASE-T SFP modules support 10/100/1000 autonegotiation and Auto MDI/MDIX.

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is

Specifications

CABLING

Туре	Category 5 unshielded twisted pair copper cabling
------	---

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	13.4 x 56.5 x 8.5 mm
Weight	0.075 kg

Used With









IE-3000-4TC

Cisco IE-3000-4TC Switch

IE-3000-8TC-E

Cisco IE-3000-8TC-E Switch w/Layer 3 IE-3000-8TC

Cisco IE-3000-8TC Switch

IE-3000-4TC-E

Cisco IE-3000-4TC-E Switch w/Layer 3







2960+24PC-L/IEC60945

Cisco Catalyst 2960+24PC-L Ethernet Switch Kit -IEC60945 Compliant

3560X-24P-L

CISCO Catalyst 3560X 24port 10/100/1000 PoE+ LAN Base

3560X-24P-S

CISCO Catalyst 3560X 24port 10/100/1000 PoE+ IP Base