

1008117010

## TMIV-1+ | Mini Video Intercom

Mini IP &amp; SIP Video Intercom



- ✓ Durable white thermoplastic front plate with one call button, and LED indicator for door status.
- ✓ Advanced Audio Technology - High sound pressure levels, automatic volume gain control, and active noise and echo cancellation for superior clarity
- ✓ Video Features - Wide-angle HD camera with excellent low-light performance, and support for RTSP and ONVIF streaming
- ✓ Flexible Installation - Options for wall or flush mounting
- ✓ Seamless Integration - Fully compatible with Zenitel Connect Pro, ICX-AlphaCom, IC-EDGE, and SIP-based systems.





### Description

The TMIV-1+ is a premium IP and SIP video intercom station designed for indoor and entrance installations in critical communication environments. Engineered by Zenitel, this compact and durable unit delivers high-fidelity audio and sharp HD video, ensuring reliable performance, effortless integration, and outstanding clarity for access control, security, and emergency communication applications.

See also: [additional documentation on wiki.zenitel.com](https://wiki.zenitel.com)

### Technical Dimensions



# Specifications

## AUDIO

Max SPL @ 0.5m	96 dB
Codecs	G.711, G.722, G.729
Frequency range, G.722 Codec	200 Hz – 7000 Hz
Audio technology	Full open duplex, switched open duplex
	Sound level detection (scream alarm)
	Automatic volume control (AVC)
	Acoustic Echo Cancellation (AEC)
	Noise cancellation
Internal speaker amplifier	10 W class D
Internal speaker	1 W
Microphone technology	Digital MEMS, omnidirectional microphone

## VIDEO

Lens	F 2.0, fixed iris
Image Sensor	1/2.5" RGB CMOS
Light Sensitivity	Down to 1 lux
Resolution	240p / 480p / 960x720p / 1440x1080p (MJPEG does not support 720p and 1080p resolution)
Frame Rate	Up to 30 FPS in 1440x1080p (30 FPS is only supported in H.264 mode, while MJPEG is limited to 10 FPS)
Supported Codecs	MJPEG, H.264
Digital PTZ	Yes
Digital Zoom	Up to 4x
Field of View	Up to 180 degrees horizontally and vertically
Parallel Video Streams	6 (1x SIP H.264, 2x HTTP MJPEG, 3x RTSP sessions)

## NETWORKING & PROTOCOLS

Application Protocols	SIP, SIPS, HTTP, HTTPS, TFTP, RTP, SRTP, RTCP, RTSP, DHCP, SNMP, Vingtor-Stentofon CCoIP®, NTP, ONVIF, WS-Discovery
IP Versions	IPv4 & IPv6
LAN protocols	Power over Ethernet (IEEE 802.3 a-f), Power over Ethernet (IEEE 802.3at), Network Access Control (IEEE 802.1x)
Supervision functions	Keep alive test, tone test, status reports
SIP Support	RFC 3261 (SIP base standard) RFC 3515 (SIP refer) RFC 2976 (SIP info), SIP using TLS, RFC 5630 SIPS URI scheme
DTMF Support	RFC 2833, 2976 (SIP info)
Integration and API	Connected to ICX-AlphaCom through AlphaCom protocol ACDP
	Connected to Zenitel Connect Pro through Zenitel Link
	ONVIF

## HARDWARE

Ethernet connector	1 x RJ45
General inputs and outputs	6 (configurable)
Outputs	12mA as LED drivers
Change-over relay (NO+NC+COM)	SELV
Power options	PoE, PoE+
PoE (power over Ethernet)	IEEE 802.3af standard, IEEE 802.3at
Power consumption	Idle 3.5W, max 12W (depending on volume)
Button backlight	LED
Call indication	Icons/colors for hearing impaired

## CONSTRUCTION

Dimensions (HxWxD)	117 x 117 x 43.5 mm / 4.6" x 4.6" x 1.7"
Dimensions after flush mount	117 x 117 x 8.5 mm / 4.6" x 4.6" x 0.3"
Weight	0.3 kg / 0.66 lbs.
Faceplate material	2 mm / 0.12" PMMA, colour printed on back side
Base / frame material	3 mm / 0.12" Aluminum alloy - A413.0, AISi12Fe, painted
Electronics cover material	Polycarbonate (translucent)
Loudspeaker poke protection, small diameter objects	Stainless steel mesh, acoustically transparent

## ENVIRONMENTAL COMPLIANCES

Ingress Protection Rating	IP44
Operating temperature range	-25° to 55° C / -13° to 131° F
Storage temperature range	-25° to 55° C / -13° to 131° F
Relative humidity	< 95% non-condensing

## APPROVALS

EMC	EN 61000-6-1, EN 61000-6-3
Safety	IEC / UL 62368-1, IECCE CB
Sustainability	RoHS, REACH

## OTHER SPECIFICATIONS

Country of manufacture	Poland
Warranty	2 Years standard warranty, extendible up to total of 5 years (additional fee)

## Accessories



### TA-2

US 2-Gang 3 1/2" Deep Backbox  
Item Number: 1008140020



### TA-3

2 1/2" Deep Flushmount Backbox for  
Turbine Compact & Mini  
Item Number: 1008140030



### TA-13

Turbine Mini On-Wall Back Box White  
Item Number: 1008140130



### TA-32

Turbine Mini On-Wall Back Box  
Item Number: 1008140320