zenitel

DATASHEET

2210020000

IP DECT Alarm Server

IP DECT Alarm Server including alarm module with 8 inputs



Description

- Complete messaging and alarm solution
- Time-saving operations
- Increased operational safety
- Efficient management of handsets
- Easy to use, install and configure
- Integrated into ACM IP DECT Solution
- Expandable to maximum 50 users (Basic License)

The IP DECT Alarm Server is an IP-based messaging platform which enables the integration of a reliable and efficient alarm and message handling system into an IP DECT communication solution onboard marine vessels. It receives, handles and distributes alarm messages. The IP DECT Alarm Server can, for example, distribute critical information regarding engine alarms, fire alarms, etc. throughout the vessel. Alarm messages can either be distributed to a group of telephones or to a single telephone.

The IP DECT Alarm Server can be easily integrated into the IP DECT Solution.

www.zenitel.com info@zenitel.com Last revision date: 2026-11-19 10:53

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL

SERVER	
Dimension (HxWxD) (mm)	65 x 213 x 107
Weight	3.8 kg
Power	10-30 VDC / Max. = 36 W, Typical = 10 W (input voltage must not exceed 30 V)
Network interface	2 x 10/100 Mbps Ethernet RJ45
Capacity	Up to 14 x 2210020001(Alarm modules), Total 112 alarms
Operating temperature	-15% to +55ºC
ALARM MODULE	
Dimension (HxWxD) (mm)	120 x 30 x 75
Weight	0.2 kg
Power	24 VDC
Communication	RS485
Capacity	8 opto inputs
Alarm Input	8 relay inputs, Expandable I/O
Alarm Output	IP DECT, Printer Log, Log File
Management and Control	112 different alarms, Web browser-based configuration tool, Text messages with 36 characters, 15 different alarm signals, Flexible time-out between 0.1 – 2250 sec, Repetition of alarms in intervals from 1 - 2550 sec

www.zenitel.com info@zenitel.com Last revision date: 2026-11-19 10:53

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

ACCESSORIES

2211000658	Back-Up CMOS Battery: Replacement Battery for Alarm Server.
9021908004	License to upgrade old COBS Alarm Server

Used With

www.zenitel.com info@zenitel.com Last revision date: 2026-11-19 10:53

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.