

2810010112

CAB24FWD-V2

Floor cabinet 19" 24HU 800x800x1200mm fixed frame



- ✓ Front door: Single steel doors
- ✓ Front door handle: CAB-DH-K
- ✓ Rear door: Single steel doors
- ✓ Rear door handle: double-bit lock
- ✓ Including 4x eyebolts for crane transportation
- ✓ The door hinged on the right, may be swapped to the left
- ✓ Base/plinth not included, can be ordered separately

Description

Our all-new series of multi-use cabinets are designed to be used in a marine environment. This floor-mounted 24HU cabinet is DNV-GL type approved and it's perfect for installing our 19" system components to create a complete system for your installation.

The cabinet comes with a front metal door that is hinged on the right, and it can be swapped to the left if needed. The rear side of the cabinet is covered with a fixed metal plate and can be replaced with rear doors if needed. Cabinet variant 24 HU, 800 wide and 800 deep. Internal 19-inch fixed frame for up to 24 HU. Includes the choice of DIN rail mounting in the bottom, prepared for optional power switch-over modules and terminals. It comes with 3 fixed door plates, front doors, and chassis ground.

By default, the cabinet is IP55 but the final IP rating will depend on the chosen ventilation options.


This cabinet is suitable for:

- ✓ ACM Advanced modules
- ✓ SPA-V2 Public Address
- ✓ EXIGO Public Address
- ✓ Radio
- ✓ LAN

- ✓ CCTV
- ✓ IPTV
- ✓ DECT
- ✓ Paging
- ✓ Masterclock
- ✓ UPS (small)

Technical Dimensions

CABINET TECHNICAL DATA	
MODEL:	RITTAL CUSTOM MODEL
COLOR:	RAL 7035
BASE WEIGHT:	125kg (275lbs)
BASE/PLINTH:	NO
VENTILATION:	NONE (DEFAULT)
FRONT DOORS:	METAL
REAR DOORS:	METAL
DOOR HANDLE:	DOOR HANDLE W/ KEY-LOCK (DEFAULT)



Specifications

GENERAL

Dimensions (WxDxH)	808x864x1263mm
Color	RAL 7035
Material	Steel
Ingress grade	IP-55 (or less, based on selected ventilation)
Mounting	Floor mounted
Cable inlet	Bottom (top available on request)
Environmental Condition	Protected

Accessories



CAB-DH-PP

Door handle with push-button & pad-lock for CABxx



CAB-DH-P

Door handle with push-button for CABxx



CAB-DH-K

Door handle with key-lock for CABxx



CAB-CE-M

Cable entry gland 14xM25/32



CAB-CE-L

Cable entry gland
2xM25/32/40, 1xM32/40/50,
2xM40/50/160



CAB-CE-S

Cable entry gland w/sealing
membranes Ø7 to 26mm



CAB-LED

CABxx LED System light
w/sensor 100-240VAC,
w/connection cable



CAB-AVIP55-115

Active IP55 ventilation for
CABxx, 133 mm height, 115
VAC



CAB-AVIP55-230

Active ventilation unit IP55 for
CABxx, 133mm height,
230VAC



CAB-AVT-115-230

Active ventilation for CABxx
with glass door, 115-230VAC



CAB-BASE-88

Base / plinth for 800x800mm
cabinets