

2810010111

## CAB24FW-V2

Floor cabinet 19" 24HU 800x600x1200mm fixed frame



- ✓ Front metal door
- ✓ Front door handle: CAB-DH-K
- ✓ Rear metal door
- ✓ Rear door handle: Double-bit lock
- ✓ Includes 2x side steel sheet panels
- ✓ Including 4x eyebolts for crane transportation
- ✓ The door hinged on the right, may be swapped to the left
- ✓ Base/plinth not included, can be ordered separately

## Description

Our all-new series of multi-use cabinets are designed to be used in a marine environment. This floor-mounted 24HU cabinet is DNV-GL type approved and's perfect for installing our 19" system components to create a complete system for your installation.

The cabinet has a front metal door hinged on the right, and it can be swapped to the left if needed. The rear side of the cabinet is covered with a fixed metal plate and can be replaced with rear doors if required. Cabinet variant 24 HU, 800 wide, and 600 deep. Internal 19-inch fixed frame for up to 24 HU. Includes the choice of DIN rail mounting in the bottom, prepared for optional power switch-over modules and terminals. It has 3 fixed door plates, front doors, and chassis ground.

By default, the cabinet is IP55 but the final IP rating will depend on the chosen ventilation options.


This cabinet is suitable for:

- ✓ ACM Advanced modules
- ✓ SPA-V2 Public Address
- ✓ EXIGO Public Address
- ✓ Radio
- ✓ LAN
- ✓ CCTV

- ✔ IPTV
- ✔ DECT
- ✔ Paging
- ✔ Masterclock
- ✔ UPS (small)

# Technical Dimensions

CABINET TECHNICAL DATA	
MODEL:	RITTAL CUSTOM MODEL
COLOR:	RAL 7035
BASE WEIGHT:	116 KG (255 LBS)
BASE/PLINTH:	NO
VENTILATION:	NONE (DEFAULT)
FRONT DOORS:	METAL
REAR DOORS:	METAL
DOOR HANDLE:	DOOR HANDLE W/ KEY-LOCK



# Specifications

## GENERAL

Dimensions (WxDxH)	808x663x1264mm
Color	RAL 7035
Material	Steel
Ingress grade	IP-55 (or less, based on selected ventilation)
Mounting	Floor mounted
Cable inlet	Bottom (top available on request)
Environmental Condition	Protected

## Accessories



### CAB-DH-PP

Door handle with push-button & pad-lock for CABxx

Item Number: 2810011064



### CAB-DH-P

Door handle with push-button for CABxx

Item Number: 2810011063



### CAB-DH-K

Door handle with key-lock for CABxx

Item Number: 2810011062



### CAB-CE-M

Cable entry gland 14xM25/32

Item Number: 2810011048



**CAB-CE-L**

Cable entry gland  
2xM25/32/40, 1xM32/40/50,  
2xM40/50/160

Item Number: 2810011049



**CAB-CE-S**

Cable entry gland w/sealing  
membranes Ø7 to 26mm

Item Number: 2810011050



**CAB-LED**

CABxx LED System light  
w/sensor 100-240VAC,  
w/connection cable

Item Number: 2810011059



**CAB-AVIP55-115**

Active IP55 ventilation for  
CABxx, 133 mm height, 115  
VAC

Item Number: 2810011068



**CAB-AVIP55-230**

Active ventilation unit IP55 for  
CABxx, 133mm height,  
230VAC

Item Number: 2810011067



**CAB-AVT-115-230**

Active ventilation for CABxx  
with glass door, 115-230VAC

Item Number: 2810011079



**CAB-BASE-86**

Base / plinth for 800x600mm  
cabinets

Item Number: 2810011090