

2310131033

Armoured Multicable 4m

4m Multicable



- ✓ Pre-cabled for Ethernet, I/o and power supply connections
- ✓ Equipped with barrier cable gland
- ✓ Made of flame retardant material
- ✓ Resistant to oil and ultra-violet rays
- ✓ Designed for potentially explosive zones



Description

The Armoured Multicable 4m is suitable for explosion-proof PTZ cameras of the Maximum MXP Series2.

Specifications

MECHANICAL

Length	4m
External diameter	20.0 mm, ± 0.5 mm
Diameter under armature	15.20 mm
Minimum bending radius	220 mm
Color	black
Type of laying	fixed installation

ELECTRICAL

Power Supply Cables	Number of conductors: 3 Section: 2.5mm ²
Signal cables	Number of conductors: 7 Section: 0.34mm ²

NETWORK (ETHERNET CABLE)

External diameter	6.1mm
Section	4 x 2 x 0.22 mm ²
Category	5e
Shielding	SF/UTP
Standard	EIA/TIA 568-B

ENVIRONMENT

Operating Temperature	from -60°C up to + 105°C *For indoors and outdoors installation
-----------------------	--

CERTIFICATIONS

Oil Resistant	Complies with CNOMO E.3.40.150N, ASTM n.2, IRM 902, VDE 0472 p.803 test B
UV Resistant	Complies with IEC 60068- 2-5
Flame Resistant	Complies with IEC/EN60332-1, IEC/EN60332-3-22, IEC/EN 60079-14(ATEX Ex II)
RoHS (CE)	Complies with 2015/863/EU