


loudspeaker

tbd

## SPPR-P-20W-50

### PROJECTOR SPEAKER

- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ 20W / 100V
- ✓ PROJECTOR SPEAKER
- ✓ SIZE 5.0" (130MM)
- ✓ U-BRACKET MOUNTING
- ✓ ROBUST ABS PLASTIC HOUSING
- ✓ WEATHERPROOF TO IP56

 Public Address Commercial Audio

## Description

The SPPR-P-20W-50 is a 20W 100V sound projector loudspeaker which has a 5" (130mm) full-range chassis providing excellent sound quality with speech and background music, . The speaker is fitted with a 100V transformer which has four power adjustment tapings of 20W, 10W, 5W and 2.5W.

The SPPR-P-20W-50 has a robust impact resistant white ABS housing, which is sealed to the IP56 environmental standard. Thus, the speaker is impervious to any objects of above 1mm diameter, is protected against the ingress of dust and is sealed against high pressure water jets. Mounting of the speaker is provided using a steel 'U' bracket, which provides a number of flexible mounting options. The 100V loudspeaker line connection is provided via a 900mm two core LSZH cable, which is terminated with an IP65 ingress protection rated connection box. In order to provide increased fire protection, the speaker is also fitted with a 2-pin ceramic block and a thermal fuse, while the speaker chassis is also damp-resistant.

This loudspeaker is optionally available with a DC blocking capacitor fitted, in order to provide compatibility with DC loudspeaker line monitoring systems. The part number for this DC monitoring compatible version is SPPR-P-20W-50-DC

## Used With



from site

D150

PAVA 150W Power Amplifier  
Module for the V2000 /  
INTEGRA

Item Number: 1200202150

from site

D500

PAVA 500W Power Amplifier  
Module for the V2000 /  
INTEGRA

Item Number: 1200202500

V2000

PAVA 2000W Power Amplifier  
Mainframe (0 amps Pre  
Installed)

Item Number: 1200202000