

loudspeaker

tbd

## SPCP-20W-65-EN54

### PENDANT CEILING SPEAKER

- ✓ EN 54-24 CERTIFIED
- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ PENDANT CEILING SPEAKER
- ✓ 20W /100V
- ✓ 6.5" (165mm) FULL RANGE CHASSIS
- ✓ INGRESS PROTECTION IP35
- ✓ UV-RESISTANT ABS HOUSING RATED TO UL94-V0

## Description

The SPCP-20W-65-EN54 is a 20W 100V pendant ceiling mount loudspeaker. It has a 6.5" (165mm) full-range loudspeaker chassis providing excellent sound quality with speech and background music. Certified to EN 54-24. The speaker is fitted with a 100V transformer which has five power adjustment tappings of 20W, 15W, 10W, 5W and 2.5W. Low impedance operation is also possible.

The SPCP-20W-65-EN54 has a sturdy, UV-resistant ABS housing rated to UL94-V0, with an ingress protection rating of IP35, and is coloured to match RAL9016 'Traffic White'. However, the speakers can be supplied in any four digit RAL or NCS colour, as a special order. The 100V loudspeaker line connection is provided via a 5m long 5-core cable, which is terminated to the 100V loudspeaker line site cabling using a two-pin ceramic block, housed within the speaker's ceiling mounting rose. For additional reliability a thermal fuse is provided and the speaker chassis is damp-resistant.

The loudspeaker is optionally available with a DC blocking capacitor fitted, in order to provide compatibility with DC loudspeaker line monitoring systems. The part number for this DC monitoring compatible version is SPCP-20W-65-EN54-DC.

## Used With

from site

from site



D150

PAVA 150W Power Amplifier  
Module for the V2000 /  
INTEGRA

Item Number: 1200202150

D500

PAVA 500W Power Amplifier  
Module for the V2000 /  
INTEGRA

Item Number: 1200202500

V2000

PAVA 2000W Power Amplifier  
Mainframe (0 amps Pre  
Installed)

Item Number: 1200202000