



1022100200

HSB-4

Analog FXS telephone, weatherproof

AVAILABLE FROM END OF Q2 2024

- Multi-purpose analog telephone
- ✓ Weather and corrosion resistant (IP66)
- O Delivered for bulkhead mounting
- Socket with dust-cap for connection of headset or microphone
- Option for connection of handset or headset
- DTMF dialing
- Potential free alarm contact for external alarm system, max 50mA
- External relay units as IRR-3 and CRB-7A can be used for activating of extra alarm



IP66

Description

The HSB-4 is a weather-proof analog telephone is well suited for installation in harsh environments and with headset operation it can also be used efficiently in any noisy areas. It is intended for bulkhead mounting and it can also installed in a PLM cabinet for additional protection of the telephone and connected accessories.


Technical Dimensions

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.


SIDE VIEW

FRONT VIEW

REAR VIEW







page 2/3

Specifications

GENERAL

Ringing voltage:	45-110 V, 25-50 Hz
Dimensions (MM)	124W x 224H x 63D
Temp. range	-20 C / +50 C
Connections	Screw terminals
Cable Inlet	2x PG-13.5
Colour	Grey with black front
IP rating	IP-66
Enclosure material	ABS/PC
Call indication	Blinking LED (recommended to use in combination with tone caller such as HB-105)

Accessories









P-MT7-A

Headset with boom mic, headband, and 10m cable

HAS-3

Handset for HSB-03 W/C16 plug

HAS-3WT

Handset for HSB-03 W/C16 plug. Weather proof

CRB-7

Relaybox for Signal Units Waterproof



HB-105-2

Telephone Tonecaller, 60-100V AC, 105 dBa, watertight, IP66

Used With

page 3/3