



2211050108

# DECT repeater 4-ch, multi-cell 1G8 with power supply

## **DECT** repeater

- Power Supply Included (PSU 100-240VAC/9.0-300mA)
- Create coverage in a remote area
- Expand coverage in a single cell solution
- Increase coverage in hot spot areas
- Oan be used with all KWS Servers
- Max 3 Repeaters per Base Station
- External power supply required

# Description

The DECT repeater 4-ch, multi-cell 1G8 with power supply provides a larger geographical spread of the traffic channels and increases the coverage area. Mainly used in areas with limited coverage such as long hallways, stairwells and corridors. The repeater is wireless with no wired connection to the KWS DECT Server or base stations, making it very easy to install. It is certified for use under Marine EMC requirements.

The DECT repeater 4-ch, multi-cell 1G8 with power supply comes with a Power Supply (PSU 100-240VAC/9.0-300mA)

Product also available in the following frequency bands:

✓ Item number 2211050109: DECT Repeater 1G9. USA & Canada. 1920–1930MHz (DECT6.0)

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

page 1/2

# **Specifications**

#### **DESCRIPTION**

Max. number of speech channels	Four
Typical range	Indoor: 20 - 50 m; Outdoor: 300 m
Weight	112.9 gr
Size	100 x 30 x 100 mm
Frequency Range	EMEA 1880-1900 MHz

### PRODUCT VARIANTS

2211050109	DECT Repeater. USA, Canada. 1G9 1920–1930MHz (DECT6.0)
2211050108	DECT Repeater. EMEA, Australia, New Zealand.1G8 1880– 1900MHz

#### **ACCESSORIES**

2211050131	Repeater Programming Kit
2241100558	Power Supply for DECT Repeater

## **Used With**









IP DECT Server 400 1G8 Version

Server Base Station

KWS2500

DECT Rack including base station card, KWS-CPU and software license

KWS8000

DECT Rack including power supply, cable and software license

KWS6500

IP DECT Server for 30 users, including software licence