

2211050109

DECT repeater 4-ch, multi-cell 1G9 with power supply

DECT repeater



- ✓ Power Supply Included (PSU 100-240VAC/9.0-300mA)
- ✓ Create coverage in a remote area
- ✓ Expand coverage in a single cell solution
- ✓ Increase coverage in hot spot areas
- ✓ Can be used with all KWS Servers
- ✓ Max 3 Repeaters per Base Station
- ✓ External power supply required

Description

The DECT repeater 4-ch, multi-cell 1G9 with power supply provides a larger geographical spread of the traffic channels and increases the coverage area. Mainly used in areas with limited coverage such as long hallways, stairwells and corridors. The repeater is wireless with no wired connection to the KWS DECT Server or base stations, making it very easy to install. It is certified for use under Marine EMC requirements.

The DECT repeater 4-ch, multi-cell 1G9 with power supply comes with a Power Supply (PSU 100-240VAC/9.0-300mA)

Product also available in the following frequency bands:

- ✓ Item number 2211050108: DECT repeater 4-ch, multi-cell 1G8 with power supply (PSU 100-240VAC/9.0-300mA)

Specifications

DESCRIPTION

Max. number of speech channels	Four
Typical range	Indoor: 20 - 50 m; Outdoor: 300 m
Weight	112.9 gr
Size	100 x 30 x 100 mm
Frequency Range	1920-1930 MHz

PRODUCT VARIANTS

2211050109	DECT Repeater. USA, Canada. 1G9 1920–1930MHz (DECT6.0)
2211050108	DECT Repeater. EMEA, Australia, New Zealand.1G8 1880– 1900MHz

ACCESSORIES

2211050131	Repeater Programming Kit
2241100558	Power Supply for DECT Repeater

Used With



IP DECT Server 400 1G8 Version

Server Base Station

Item Number: 2211010200



KWS2500

DECT Rack including base station card,
KWS-CPU and software license

Item Number: 2211020100



KWS8000

DECT Rack including power supply, cable
and software license

Item Number: 2211020106



KWS6500

IP DECT Server for 30 users, including
software licence

Item Number: 2211000150