



2340110047

SPA-M1-V2-MED

PA Panel Single, All-Call, Flush, Green Backlight



MED Certification



Onboard communication

Description

- ✓ PA Panel for single system, all call
- Built-in pre-amplifier with preset signal level and tone controls
- TALK button on panel
- Flush mounting, back box for wall mounting is available
- Local mute contact for external loudspeaker
- Buttons backlight with green illumination

This panel gives All Call Message in a SPA-V2 public address and general alarm single system. Installation in consoles or wall indoor.


Local mute function is used to break audio to loudspeakers where proximity to pa panel cause feedback. This function


page 1/4

must be in combination with relay box.

Note: Microphone must be ordered separately.

Technical Dimensions





Related item: SPA-M6BOKS Wall mounting box for SPA-M1/M6 panels Item.no. 3005010155 MB-30G Gooseneck Microphone Item.no.3005020033 ETC-1-TB Hand Microphone Item.no.3005020029


Specifications

GENERAL

Size (WxHxD)	144 x 144 x 82
Weight w/microphone	0. 5 kg
Material	Black anodized aluminium
Mounting	Flush, wall with use of back box
Output signal	0.775Vrms / 0dB
Connections	Plugable screw terminals for 2.5 mm2 cable
Cable glands	2 x PG-16
Cable size	6 x 2 x 0.75mm2
Local mute relay, output	24V DC @ maximum 50 mA
IP-rating	IP-44
EN60945 environmental category	Protected
Compass safe distance	0.75 m
Operator & reading distance	0.7m

Accessories

page 3/4





Wall-mount box for SPA-M1/M6 and VM15/50-RD panels



MB-30G

Gooseneck Microphone



PAM2H

Handheld Microphone for SPA-V2 indoor panels.