



2211100135

ATEX Handset FC4 EX

DECT handset

- Explosion protection for gas in zones 1 and 2
- ✓ IP65
- ✓ Up to 92 dB volume
- Individual signaling for internal, external and messaging alerts
- ✓ Hot key for local phone book with 500 entries
- ✓ User-replaceable Li-lon battery
- Speaker for hands-free operation



Description

The ATEX Handset FC4 EX has an illuminated high-resolution color display, a newly designed symbol-based user interface and an illuminated keypad containing color function keys.

The ATEX Handset FC4 EX battery can be easily changed by the user and offers state-of-the-art power management. Combined with highly individualized configuration of usage, signaling, messaging functions and outstanding communication lists, the handset is the perfect professional communication tool, resulting in a high level of security, while offering easy operation and exact information.

The ATEX Handset FC4 EXis a safe, robust industrial handset with DECT-based integrated voice-data communication and explosion protection. It is certified for usage within hazardous areas and fulfils the latest European ATEX guideline.

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

TECHNICAL DATA

Dimensions	approx. 141 x 47 x 35 mm
Weight (including battery)	approx. 133 g
Explosion protection zone 1 and 2	Gas according to ATEX 2014/34/EU: II 2 G Ex ib IIC T4 Gb
Degree of protection	IP 65 (water-jet protected and dust-proof)
Lithium-ion battery, replaceable	700 mAh (screw-fastened)
Charging time	approx. 5 h
Battery life Stand-by	32 – 150 h
Battery life Talking time	12 – 17 h
Frequency range	1.88 1,9 GHz
Transmission power	Average 10 mW, peak 250 mW
Acoustic signaling	up to 93 dB(A) within a distance of 30 cm
Speaker	rear-mounted
Hands-free talking	very good voice intelligibility
Vibration alarm	additional or silent alarm

page 2/2

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.