

MT15H7AWS6-111

WS ProTac XPI Bluetooth Headset, Headband, FLX2

Hearing protection headset with Bluetooth connectivity, level-dependent ambient listening and an FLX2 connection for compatible two-way radios.

- Bluetooth connectivity for wireless communication with compatible devices.
- Bluetooth Multipoint for connecting up to two external devices.
- Level-dependent ambient listening to help users hear surrounding sounds while wearing hearing protection.
- Noise-cancelling boom microphone for speech transmission in noisy environments.
- FLX2 connector for wired connection to compatible two-way radios using the appropriate cable.
- Headband design.
- Bright yellow colour.

Description

WS ProTac XPI Bluetooth Headset

The WS ProTac XPI Bluetooth Headset is a hearing protection headset designed for communication in noisy working environments. The MT15H7AWS6-111 model combines Bluetooth connectivity, level-dependent ambient listening and an FLX2 connector for use with compatible two-way radios.

The headset features a noise-cancelling boom microphone for speech transmission and level-dependent technology that allows users to hear surrounding sounds without removing their hearing protection. Bluetooth Multipoint supports connections to up to two external devices.

The FLX2 connector provides a wired connection option for compatible two-way radios. The appropriate FLX2 cable must be selected for the radio in use, and compatibility should be verified for the intended setup.

The headband design and bright yellow colour make this model easy to identify in working environments where hearing protection and reliable communication are important.

www.zenitel.com info@zenitel.com Last revision date: 2026-11-19 13:04

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL SPECIFICATIONS

Attachment wire	Stainless steel
Two-point fastener	Acetal
Operating temperature	-20°C to +50°C (battery dependent)
Operating time	Approximately 45 hours of battery lifetime with included alkaline batteries
Bluetooth Version	4.2+EDR
Bluetooth Frequency	2400-2483.5 MHz
Supported profiles	HF/HS version 1.5, A2DP version 1.2
Output power	2,5 mW
Menu Language	English
Recommended storage conditions	-20º C - +50º C, <90% humidity
Recommended max. shelf life	5 years except the batteries, <1 year

www.zenitel.com info@zenitel.com Last revision date: 2026-11-19 13:04

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.