

3006102015

BEX-2300

Explosion Proof Xenon Beacon 5 Joule 230V



 IP66

 IP67

 Ex Atex

DESCRIPTION

- Marine grade, corrosion proof, LM6 aluminium enclosure
- IP66/IP67 ingress protection
- 120 candela effective light intensity
- Orange

The flameproof BEX-2300 Xenon beacons are suitable for Zone 1, 2, 21 & 22 applications. Approved to IECEx, ATEX, Ex EAC and INMETRO standards.

SPECIFICATIONS

GENERAL

Weight	2.75 kg
Energy	5 Joules (5Ws)
Flash rate	1 Hz (60 fpm)
Peak Candela	500,000 cd - calculated from energy (J)
Eff. Intensity cd	250 cd - calculated from energy (J)
Cable entries	2x M20 ISO (One cable gland and one blind plug incl.)
Temperature range	-50° to +70°C
Relative humidity	90% at 20°C
Housing material	Marine grade LM6 aluminium

ORDER NUMBER	DESCRIPTION
3006102016	BEX-230B Beacon Ex BExBG05D 230V AC blue ATEX IP67 1x cable gland
3006102085	BEX-230G Beacon Ex BExBG05D 230V AC green ATEX IP67 1x cable gland
3006102086	BEX-230R Beacon Ex BExBG05D 230V AC red ATEX IP67 1x cable gland
3006090474	BEX-230Y Beacon Ex BExBG05D 230V AC yellow ATEX IP67 1x cable gland
3006102015	BEX-2300 Beacon Ex BExBG05D 230V AC Orange ATEX IP67 1x cable gland

TECHNICAL DIMENSIONS

