

3006100056

HP-15TF

Hornspeaker 15W

 IP66

 IP67



DESCRIPTION

- Horn Loudspeaker for open deck and machinery spaces.
- Excellent for P.A. / Intercom
- With transformer for 100V amplifier line
- 2x M20 cable gland and fuse

To install the loudspeaker:

- Fasten loudspeaker to wall/ceiling with two screws through foot bracket.
- Remove lid by 1 screw, lead cable through cable gland, select required tapping and connect to terminal
- To change the position of the loudspeaker please adjust the bracket (by loosening / tightening the screws) as required.

For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated. Do not open loudspeaker when energized.

SPECIFICATIONS

GENERAL

Material / Colour	ASA / RAL 7035
Dimensions	Ø 200 x 250D
Mounting	Bracket
Termination	Inside screw connections
Weight	1,7 kg
Max. / min. amb. temp	90°C / -50°C
Rated / Max power	15W / 20W
SPL 1W / 1 m	108 dB
SPL rated power	118 dB
Effective freq. range	330-8000 Hz
Dispersion (-6dB) 1kHz / 4kHz	130° / 35°
Directivity factor, Q	8,3
Ingress protection	IP66/67

TECHNICAL DIMENSIONS

