

1023533013

PAM2H

Handheld Microphone for SPA-V2 indoor panels.



Onboard communication



- Handheld microphone for SPA-V2 indoor microphone panels.
- Bracket included
- Push-To-Talk button
- 1.5 m durable spiral cable
- Equipped with locking DIN plug
- Dynamic microphone
- Unidirectional noise cancelling
- Rugged brass housing
- Very long life switching contacts

DESCRIPTION

The PAM2H handheld microphone is designed for indoor use, even in noisy areas with unidirectional noise cancelling. The microphone is used on all SPA-V2 microphone panels and features a PTT button.

SPECIFICATIONS

ITEM NUMBER	DESCRIPTION
1023533013	PAM2H Handheld PA microphone, 1 button, indoor, w/bracket. Dynamic
MECHANICAL	
Dimensions	Length 178 mm, Head Ø 29 mm, Body Ø 24 mm
Weight	0.23 kg
Cable	4-wire halogen free spiral cable, 2 Wires shielded, Draw length max. 1.5 m, without connector
Material	Brass. Black
Bracket	Included
ELECTRICAL	
Microphone	Dynamic and Noise Cancelling
Frequency range	150 Hz to 12 kHz at -10 dB
Sensitivity	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance	200 Ω ± 20 % at 1 kHz
Directivity	Cardioid (at 1 kHz; 180° -20 dB)
ENVIRONMENTAL	
Operating Temperature	-20 °C to +60 °C
Storage Temperature	-30 °C to +70 °C
Humidity	10% to 95% (non-condensing)
COMPATIBLE EQUIPMENT	
SPA-V2 Indoor panels	

TECHNICAL DIMENSIONS

Will come shortly!

ACCESSORIES



ETC-1-CH

Item Number: 3005020028



ETC-1/CABLE

Item Number: 3005020027

USED WITH



2340110020

SPA-M6-V2

PA Panel Single with 6 zones, All Call, Dimmer, Flush

2340110021

SPA-M6-D

PA Panel Dual with 6 Zones, All Call, Dimmer, Flush



3005010150

SPA-M1-V2

PA Panel Single, All-Call, Flush



2340110019

SPA-M1-D

PA Panel Dual, All-Call, Flush

