

119010010x

Recording Software

Vingtor-Stentofon



DISCONTINUED

DESCRIPTION

- SIP-based active recording for AlphaCom XE
- Easy installation - just connect recorder server to IP network
- Records conversations involving any type of terminal connected to AlphaCom
- Records conversations, group/all calls, and conference calls
- Compatible with AlphaCom E and XE
- Enterprise, Standard and Lite versions - scales well for environments with different recording capacity and playback needs
- RSA digitally signed audio and metadata - enables detection of tampering
- Fully featured audio playback client
- Search on call metadata

The Vingtor-Stentofon Recording Software is a fully-featured IP based audio recorder for the AlphaCom audio server. The solution is able to record calls from all types of terminals connected to AlphaCom: analog intercoms, IP intercoms, analog phones, and IP phones.

For each conversation that needs to be recorded, AlphaCom sets up a SIP call session to the Vingtor-Stentofon Recording Software. The call session includes metadata about the parties in the conversation and the conversation type – conversation, group/all call, conference. This mode of operation allows for the Vingtor-Stentofon Recording Software to be located anywhere in the IP network, and even to receive call recording data from multiple AlphaCom audio servers at the same time.

SPECIFICATIONS

SPECIFICATION SERVER	RECORDING SOFTWARE LITE	RECORDING SOFTWARE STANDARD	RECORDING SOFTWARE ENTERPRISE
Networking	One AlphaCom server	Multiple AlphaCom servers	Multiple AlphaCom servers
Number of recorded stations/conferences	Max. 10	Max. 250	Max. 2000

Created: 10.07.2014, updated: 21.01.2021

page 1/2

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

SPECIFICATION SERVER	RECORDING SOFTWARE LITE	RECORDING SOFTWARE STANDARD	RECORDING SOFTWARE ENTERPRISE
Simultaneous recordings	5 calls	20 calls	100 calls - recording server, 30 calls per AlphaCom server
Playback client	Playback client runs on same computer as recording server	Playback client runs on same computer as recording server	Playback client can run on any client PC on the same network
Simultaneous playback	1	1	2 (default), Additional require license
Customized playback client	No	No	Yes, SDK available
Recording format	G.711 (Narrowband voice) and G.722 (Wideband voice)		
Watermarking	RSA digitally signed		
Archiving	Recording can be archived on different servers, hard drive or media		
Compatible AlphaCom	AlphaCom E or AlphaCom XE servers with software version 11.2.3.0 or higher		
Supported AlphaCom stations	Traditional intercom, IP Intercom, Analogue telephones, IP telephones (SIP), IP-ARIO (PA and radio interface)		
Supported call types	Two way conversations, Local group calls, Global group calls, Simplex conference, Duplex conference		

RECOMMENDED MINIMUM REQUIREMENTS

Vingtor-Stentofon Recording Software	Lite	Standard	Enterprise
Operating system	Windows 7 or later	Windows 7 or later	Windows 7 or later/Windows Server 2008 or later
Software dependency	NET 3.5 Framework SP1	.NET 3.5 Framework SP1	.NET 3.5 Framework SP1
Processor	Intel Pentium Dual-Core E5400	Intel Core2 Duo E8600 processor	Intel Quad Core Xeon E5440 processor
Memory	1 GByte	2 GByte	4 GByte
Hard Disk, CallHours @ 1RTP stream per conversation, CallHours @ 2 RTP streams per conversation	> 100 GByte recommended, 3600, 1800	> 320GByte recommended, 11000, 5700	> 1 TByte recommended 38000 , 19000
Hard disk transfer speed	480 Mbit/sec	1.5 Gbit/sec	1.5 Gbit/sec
Hard disk with Raid technology			Recommended
Network speed	100 Mbit/sec	100 Mbit/sec	1 Gbit/sec
Sound Card	Required	Required	Optional, required when Playback , Client resides on the same PC
Speakers	Required	Required	Optional, required when Playback, Client resides on the same PC

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
1009648092	Active recording interface - 2 users	
1009648093	Active recording interface - 6 users	
1009648094	Active recording interface - 12 users	
1009648095	Active recording interface - 36 users	
1009648096	Active recording interface - 72 users	
1009648097	Active recording interface - 138 users	
1009648098	Active recording interface - 276 users	
1009648099	Active recording interface - 552 users	
1190100100	Vingtor-Stentofon Recording Software – Lite	
1190100101	Vingtor-Stentofon Recording Software – Standard	
1190100102	Vingtor-Stentofon Recording Software – Enterprise	
1190100103	Vingtor-Stentofon Recording Playback Client License	

Note 1 : Lecture des messages d'enregistrement uniquement à partir de l'ordinateur hébergeant le logiciel d'enregistrement.

Note 2 : L'applicatif de lecture des messages d'enregistrement peut être mis en réseau avec le serveur d'enregistrement.