

2320000618

SEAS T4-20

Tap-Off, 4 way (+20dB) (TV, R) with F-connectors



DESCRIPTION

- Digital-analogue splitters for marine use 100 kHz-1000 MHz
- Isolated 5 mm base, to avoid grounding to hull, to make it double isolated
- Linear frequency response up to 1000 MHz
- Excellent port isolation
- Nickel plated HQ housing

SPECIFICATIONS

TECHNICAL SPECIFICATION

Dimension (HxWxD) (mm)	(H) 46 x (W) 76 x (D) 32 mm
Bottom spacer	PP, RAL5003 Dark Blue
Housing	Zinc Die-casting - finishing: CuSn Plated
Connectors	"F" Female
Weight	0.160 Kg
Insertion Loss (dB) IN-OUT 100~500 KHz	11 max.
Insertion Loss (dB) IN-OUT 0.5~5 MHz	3 typ. 4.5 max.
Insertion Loss (dB) IN-OUT 5~300 MHz	3.5 typ. 4.5 max.
Insertion Loss (dB) IN-OUT 300~860 MHz	3.5 typ. 4.5 max..

Created: 08.06.2016, updated: 24.03.2022

page 1/3

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel - All rights reserved.

TECHNICAL SPECIFICATION

Insertion Loss (dB) IN-OUT 860~1000 MHz	3.8 typ. 4.5 max.
Tap loss IN-TAP 100~500 KHz	31.5 max.
Tap loss IN-TAP 0.5~5 MHz	21 typ. 23 max.
Tap loss IN-TAP 5~300 MHz	20 +/- 1
Tap loss IN-TAP 300~860 MHz	20 +/- 1.5
Tap loss IN-TAP 860~1000 MHz	20 +/- 1.5
Isolation TAP-OUT 5~40 MHz	30 min.
Isolation TAP-OUT 40~300 MHz	30 min.
Isolation TAP-OUT 300~860 MHz	24 min.
Isolation TAP-OUT 860~1000 MHz	24 min.
Isolation TAP-TAP 5~40 MHz	40 min.
Isolation TAP-TAP 40~300 MHz	40 min.
Isolation TAP-TAP 300~860 MHz	36 min.
Isolation TAP-TAP 860~1000 MHz	34 min.
Return Loss**IN (dB) 5~20 MHz	
Return Loss**IN (dB) 5~40 MHz	
Return Loss**IN (dB) 40~1000 MHz	
Return Loss**IN (dB) 5~40 MHz	12 min.
Return Loss**IN (dB) 40~1000 MHz	20*
Return Loss** OUT (dB) 5~20 MHz	
Return Loss** OUT (dB) 20~40 MHz	
Return Loss** OUT (dB) 40~1000 MHz	
Return Loss** OUT (dB) 5~40 MHz	16 min.
Return Loss** OUT (dB) 40~860 MHz	20*
Return Loss** OUT (dB) 860~1000 MHz	20*
Return Loss** TAP (dB) 5~20 MHz	
Return Loss** TAP (dB) 20~40 MHz	
Return Loss** TAP (dB) 40~1000 MHz	
Return Loss** TAP (dB) 5~40 MHz	12 min.
Return Loss** TAP (dB) 40~860 MHz	20*
Return Loss** TAP (dB) 860~1000 MHz	20*
Impedance	75 Ohms
Screening factor	Class A
Operating temp.	-40 to +60°C
Approvals	CE50083-2:2006 (Class A)

*) At 40 MHz - 1.5 dB/ OCT

**) The tolerance of Return Loss Measurement: +/- 1.0 dB

TECHNICAL DIMENSIONS

