

Unified Critical Communication

- To hear, be heard and be understood, every time and everywhere



Product Catalogue



Welcome!

Zenitel product catalogue 2026

In environments where seconds matter, Zenitel helps organisations ensure **every critical message is heard**, understood, and acted upon. Our solutions are built to enhance safety, security, and operational efficiency - when it matters most.

Zenitel is moving beyond standalone systems toward a **unified critical communication approach**, bringing intercom, IP audio, PAVA and related technologies into a cohesive, scalable platform. With **Zenitel Connect Pro**, we enable clearer integration, interoperability, and a stronger connection between critical communication and the wider security ecosystem.

At the same time, Zenitel is expanding lifecycle support with **cloud-assisted monitoring and remote management**, helping customers and partners maintain performance across sites, reduce downtime, and operate more proactively.

Welcome to the 2026 Zenitel Product Catalogue - your overview of unified critical communication solutions designed for clarity, resilience, and long-term value.

Contents

4	Zenitel Connect Pro - Unified Critical Communication Platform	4
	Zenitel Cloud - Remote Monitoring & Management	6
	PAVA - Public Address and Voice Alarm	8
	Segment Solutions	10
12	Audio Intercom	12
	Video Intercom	16
	Door Intercom	19
	Intercom Accessories	20
24	Desktop , Control Room & Clean Room Stations	24
	Accessories	27
32	Industrial & EX IP Intercom	32
	Industrial & EX IP Station Accessories	35
	Flowire Converter	37
	Heavy Duty IP Stations	38
40	PAVA - Products (VIPEDIA, amplifiers, accessories)	40
	SIP Amplifiers	43
	PAVA Accessories	44
	IP Speakers	46
48	IP Station Kits	48
	IP Station Kit Accessories	51
52	Zenitel Connect Pro - Products & licenses	52
	Cloud Device Monitoring & Management	55
	ICX-510 Accessories	56
58	ICX-AlphaCom	58
	IC-EDGE Licenses	64

Zenitel Connect Pro


Unified Critical Communication Platform

Zenitel Connect Pro is the unified critical communication platform for safety and security operations, bringing intercom, IP speakers, public address, voice alarm, and general alarm into one cohesive, software-driven system.

By connecting what operators see with what they hear, Zenitel Connect Pro strengthens situational awareness and speeds up coordinated response across control room workflows and on-site teams. The platform integrates smoothly with video, access control, and third-party security systems - built on open standards such as SIP and ONVIF, and supported by Zenitel Link interfaces (REST API + PubSub) for deeper integration.

Zenitel Connect Pro offers flexible deployment options: install on a dedicated ICX-510 server or in supported x64 virtualized environments. System configuration and daily operations are managed via web, and the platform supports native audio and video communications for modern operator workflows.

When required, Cloud Connection can be enabled to support cloud-assisted monitoring and remote management, helping partners and customers maintain system health across sites more efficiently.



Seamless Integration

Open standards (SIP, ONVIF) and Zenitel Link APIs (REST + PubSub) simplify integration with VMS, access control, and security platforms—reducing project risk and accelerating time to value. For tailored site logic, native Node-RED support enables customised automation workflows tightly integrated with security platforms.

Resilient Communication

Unifying multiple communication technologies reduces reliance on a single channel and strengthens resilience across daily operations and emergencies. A single platform helps maintain consistent procedures and clear communications across sites - also when parts of the wider ecosystem are degraded.

Faster Response


Unified workflows link audio, video, and events—supporting faster incident verification, clearer coordination, and more confident decision-making in the moment. Integrated communications reduce handoffs between tools and help operators act on real-time operational signals.

Simplified Operation

One interface reduces operator training time and standardises operations across sites. Web-based administration, scalable software-driven architecture, and service-ready workflows support predictable lifecycle management - reducing on-site interventions and improving operational readiness over time.


Zenitel Cloud - Remote Monitoring & Management

Zenitel Cloud Remote Monitoring & Management (ZC-RMM) is the cloud companion to Zenitel Connect Pro, unifying visibility and operational control of Zenitel devices across customers and sites. Partners anchor deployments with Zenitel Connect Pro, enabling quick onboarding via Device Cloud ID and automatic organization of connected endpoints.



With a unified live dashboard and focused service workflows, ZC-RMM helps service teams detect issues early, reduce on-site visits, and deliver a calmer, more predictable service experience across multi-site estates.

Designed to support managed services and SLA-based offerings, ZC-RMM enables scalable operations with secure multi-customer separation and role-based control.



Secure

Security by design with least-privilege access and encrypted communications. Customer and Space scoping plus role-based permissions keep data and actions contained. Zenitel Cloud RMM is positioned with alignment to ISO 27001 and compliance statements for GDPR and SOC 2.



Centralised

One cloud interface provides unified visibility across customer projects and sites, with at-a-glance health and trends for the full estate.



Proactive

Continuous monitoring helps detect anomalies early and accelerate fault isolation - moving from reactive checks to proactive maintenance.



Operational

Practical workflows for real service work: guided claiming/onboarding, maintenance windows, bulk actions, and lifecycle tools that reduce downtime and truck rolls.

PAVA

Public Address and Voice Alarm

Zenitel's Public Address and Voice Alarm solutions deliver clear, reliable audio for public address, voice evacuation and life-safety messaging. The same platform can also support operational announcements and background music, helping organisations manage both daily communication and critical events.

In an emergency, voice-assisted evacuation enables location-specific messaging and phased guidance, helping reduce confusion and accelerate response compared to traditional alarm tones. Beyond fire scenarios, PAVA also supports mass notification and security announcements for situations such as lockdowns, industrial incidents and other evolving threats.

Designed as part of Zenitel's Unified Critical Communication offering, PAVA helps keep people informed, protect facilities and maintain calmer, more predictable operations across regulated and safety-critical environments.



Clear intelligibility

High speech intelligibility for emergency and operational messages, with consistent coverage in challenging acoustic environments.

EN 54-16

Life-safety ready

Designed for regulated life-safety environments with EN 54-aligned architectures, with EN 54-16 referenced across the portfolio. Additional certifications may apply depending on solution and market.




Resilient operation

End-to-end monitoring and comprehensive fault reporting across the audio chain support dependable operation when it matters most.



Integrated workflows

Designed to interface with life-safety and security ecosystems such as fire alarm interfaces, as well as CCTV/VMS and access control workflows.



Scalable architecture

Modular architectures scale from smaller facilities to large, complex estates, with options for centralised or decentralised design and multiple levels of redundancy for higher serviceability.

Explore the PAVA portfolio
See VIPEDIA, amplifiers and accessories in the product section.

Segment Solutions

Critical communication tailored to each segment

Zenitel supports segment-specific communication needs through one unified platform approach. Across corporate & public, transportation, industrial, healthcare, correctional and education environments, Zenitel combines intercom, IP audio, public address and lifecycle support to enable safer and more consistent response.

Corporate & Public

Critical communication across entrances, buildings and campuses.

Transportation

Help points, staff communication and operational announcements for stations, terminals and infrastructure.

Industrial

Rugged communication for high-noise, harsh and safety-critical environments.

Healthcare

Secure communication for critical areas, controlled access points and staff coordination.

Prisons

Robust communication for high-security operations, including emergency call points and controlled announcements.

Education

Unified campus communication for entrances, shared areas and emergency messaging.

One unified platform across all segments

Zenitel's unified approach connects segment-specific needs to one scalable platform model, combining intercom, IP audio, PAVA and cloud-assisted lifecycle support.

Zenitel Connect Pro

Unifies operator workflows by bringing intercom, IP audio and integrations into one operational experience across sites and systems.

PAVA

Adds trusted public address and voice alarm capabilities for regulated areas and life-safety applications where these functions are required.

ZC-RMM

Provides central visibility, proactive monitoring, diagnostics and lifecycle support to help maintain performance across distributed and multi-site deployments.



Interoperability

Zenitel Connect Pro enables unified workflows across systems by integrating critical communication with wider security ecosystems.



Scalability

Solutions scale from single sites to multi-site estates, supported by flexible deployment models and modular expansion.



Reliability

Supervision, fault reporting and resilient architectures support dependable operation for everyday use and critical events.



Ease of Use

Designed with intuitive interfaces, ensuring that personnel can act faster and more consistently under pressure.



Audio Intercom

Zenitel's Intercom Legacy: The STENTOFON Story

Zenitel's intercom heritage is deeply rooted in Norway's STENTOFON legacy. Founded in 1946 as Stentor Radiofabrikk, the company initially built radios for ships and fishing boats before expanding into STENTOFON intercom systems - earning a reputation for reliable communication in demanding environments.

Over time, these foundations evolved from analogue systems into microprocessor-based platforms, and later into IP/VoIP intercom technology with modern protocols and video-enabled capabilities. Through key milestones - including the formation of Stento ASA and the subsequent integration that became the Zenitel group - this legacy became the backbone of today's Zenitel IP intercom offering. In 2014, Zenitel further strengthened its portfolio by unifying the Vingtor and Stentofon product brands under one global Zenitel brand.

Zenitel's IP & SIP Intercom

Key Features

- **Superior audio performance** - powered by advanced audio features such as high Sound Pressure Levels (SPL) Automatic Volume Control, Active Noise Cancelling, Voice Activity Detection and Acoustic Echo Cancellation to ensure crystal-clear audio in any environment.
- **Weather-Resistant** - IP-rated for resistance to dust, dirt, and water.
- **Rugged construction** - High impact protection rating for rugged environments
- **Advanced Supervision** - Continuous monitoring with line and tone tests for system integrity.
- **Cybersecurity Hardened** - Meets industry security standards to protect against cyber threats.
- **IP-Based Connectivity** - Supports a wide set of IP and networking standards for seamless integration.
- **Power over Ethernet (PoE)** - Simplifies installation and reduces cabling requirements.

ZENITEL CONNECT PRO ICX-AlphaCom IC-EDGE SIP Onvif



TCIS-1
1008111010
IP and SIP Intercom

- LED lit call button, and two PTT buttons M (manual speech) and C (cancel)

IP66 IK08

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 0.8kg



TCIS-2
1008111020
IP and SIP Intercom

- LED lit call button
- 3mm stainless steel faceplate

IP66 IK10

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 0.8kg



TCIS-2+
1008311020
IP and SIP Intercom

- LED lit call button
- 3mm stainless steel faceplate
- ESD resilient design

IP66 IK10

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 0.8kg



TCIS-3
100811030
IP and SIP Intercom

- LED lit call button
- Door open LED indicator

IP66 IK08

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 0.8kg



TCIS-3+
100831030
IP and SIP Intercom

- LED lit call button
- Door open LED indicator
- ESD resilient design

IP66 IK08

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 0.8kg



TCIS-4
100811040
IP and SIP Intercom

- LED lit and labelled call button
- Call and door open LED indicators
- PMOLED display

IP66 IK08

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 0.8kg



TCIS-4C8
100811908
IP and SIP Intercom

- One LED lit Emergency call button with Braille, and LED indicator for call status.
- 3mm stainless steel faceplate

IP66 IK10

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 0.8kg



TMIS-1
100811610
IP and SIP Mini Intercom

- LED lit call button
- Call and door open LED indicators

IP42

Dimensions:

- Size (HxWxD): 117 x 117 x 39mm
- Weight: 0.3kg



TMIS-4
100811640
IP and SIP Mini Intercom - 2 Buttons

- LED lit call and PTT buttons
- Call and door open LED indicators

IP42

Dimensions:

- Size (HxWxD): 117 x 117 x 39mm
- Weight: 0.3kg



TCIS-5
100811050
IP and SIP Intercom

- Two LED lit and labelled call buttons
- Call and door open LED indicators
- Two PMOLED displays
- Storage for two addresses for outgoing calls

IP66 IK08

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 0.8kg



TCIS-6
100811060
IP and SIP Intercom

- Four LED lit buttons for scrolling, call and cancel
- Call and door open LED indicators
- PMOLED display
- Storage for up to 50 addresses

IP66 IK08

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 0.8kg



TCIS-C1
100811901
IP and SIP Intercom

- Two LED lit and labelled call-buttons and Braille
- Provides storage for two addresses for outgoing calls

IP66 IK08

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 0.8kg



VR3G-1
1008021010
Vandal Resistant, 3 gang, 1 button IP and SIP Intercom

- One call button
- LED lit call indicator
- 3mm stainless steel faceplate
- Tamper switch

IP66 IK10

Dimensions:

- Size (HxWxD): 160 x 114 x 60mm
- Weight: 0.73kg



VR3G-1P
1008021015
Vandal Resistant, 3 gang, 1 Piezo button IP and SIP Intercom

- Piezo Call Button with Self-test capability
- LED lit call indicator
- 3mm stainless steel faceplate
- Tamper switch

IP66 IK10

Dimensions:

- Size (HxWxD): 160 x 114 x 60mm
- Weight: 0.73kg



IPVRS-1
1008041200
Vandal Resistant IP and SIP Intercom

- One call button
- LED lit call indicator
- 2mm stainless steel faceplate
- 2 Relay outputs

IP55 IK08

Dimensions:

- Size (HxWxD): 180 x 92 x 46mm
- Weight: 0.8kg

Video Intercom




Zenitel's IP & SIP Video Intercom

Key features

- **HD Video Resolution** - Delivers clear, sharp video for better identification and communication.
- **Wide-Angle Camera** - Provides a broad view of the surroundings for enhanced security and visibility.
- **Superior Audio Performance** - High Sound Pressure Levels (SPL), Active Noise Cancelling, Automatic Volume Control, and Acoustic Echo Cancellation ensure crystal-clear audio in any environment.
- **Weather-Resistant** - IP-rated for resistance to dust, dirt, and water.
- **Rugged construction** - High impact protection rating for rugged environments
- **Cybersecurity Hardened** - Meets industry security standards to protect against cyber threats.
- **IP-Based Connectivity** - Supports a wide set of IP and networking standards for seamless integration.

ZENITEL CONNECT PRO | ICX-AlphaCom | IC-EDGE | SIP | ONVIF




TEIV-1+
1008317110
Turbine Extended IP Video Intercom with Keypad and Display

- Full numeric LED lit keypad with scroll, confirm and cancel keys
- Call and door open LED indicators
- Can operate door controller via I/O relay

IP66 IK08

Dimensions:
• Size (HxWxD): 305 x 120 x 72.5mm
• Weight: 1.08kg



TEIV-4+
1008318240
Turbine Extended IP Video with RFID card reader space

- Easy installation of access control end-points
- Call and door open LED indicators
- Includes space for 3rd party Card Readers

IP66 IK08

Dimensions:
• Size (HxWxD): 305 x 120 x 72.5mm
• Weight: 1.05kg



TCIV-2+
1008315020
IP and SIP Video Intercom

- One call button
- 3mm stainless steel faceplate

IP66 IK10

Dimensions:
• Size (HxWxD): 180 x 120 x 73mm
• Weight: 1kg



TCIV-3+
1008315030
IP and SIP Video Intercom

- One call button
- Door open LED indicator

IP66 IK08

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 1kg



TCIV-5+
1008315050
IP and SIP Video Intercom

- Two call buttons
- Call and door open LED indicators
- Two PMOLED displays
- Provides storage for two addresses for outgoing calls

IP66 IK08

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 1kg



TCIV-6+
1008315060
IP and SIP Video Intercom

- Four buttons for scrolling, call and cancel
- Call and door open LED indicators
- One PMOLED display
- Provides storage for up to 50 addresses for outgoing calls

IP66 IK08

Dimensions:

- Size (HxWxD): 180 x 120 x 73mm
- Weight: 1kg



TMIV-1+
1008117010
IP and SIP Mini Video Intercom

- One call button
- Call and door open LED indicators

IP44

Dimensions:

- Size (HxWxD): 117 x 117 x 43.5mm
- Weight: 0.3kg

Zenitel's New Door Intercoms

Two IP video door intercoms for modern access control - designed for confident visitor verification, clear conversations in real-world noise, and straightforward integration into building systems.

ZDD-1 - A premium door station for multi-tenant and corporate entrances, combining a bright 7" touch display with powerful audio and wide-angle HD video for an intuitive visitor experience.

ZSD-1 - A compact, mullion-mounted door station for narrow frames - delivering strong audio performance and wide FoV video in a slim footprint.

Both stations combine wide-angle HD video with Digital PTZ for quick visitor verification, while HD voice with Open Duplex and advanced noise/echo control delivers clear, natural conversations. Designed for secure, standards-based deployments, the stations support HTTPS, SRTP and 802.1X, and integrate smoothly via SIP/SIPS, ONVIF and RTSP. Built for harsh environments, they combine IP66 / IK08 protection with a -25°C to +55°C operating range, and PoE power options simplify installation by reducing cabling and accelerating rollout.



ZDD-1
1008510101
IP Video Intercom with Display

- 7" TFT LCD display
- Touch screen with intuitive menu and user-friendly interface
- Slim, space-saving design for modern entrances

IP66 IK08

Dimensions:

- Size (HxWxD): 281 x 176 x 44.5mm
- Weight: 1.7kg



ZSD-1
1008325010
Slim IP Video Intercom

- Designed for mullion mounting
- LED-lit call button
- Slim design for tight spaces and door-frame installations

IP66 IK08

Dimensions:

- Size (HxWxD): 197 x 48 x 31mm
- Weight: 0.2kg

Intercom Accessories

On Wall Back Boxes

new



TA-35
1008140350
Onwall Backbox

Used with:

- ZDD-1

Dimensions:

- Size (HxWxD): 281 x 176 x 27mm
- Weight: 0.2kg



TA-1
1008140010
Turbine Compact On-wall Back Box

Used with:

- TCIS Series
- TCIV+ Series

Dimensions:

- Size (HxWxD): 180 x 120 x 66mm
- Weight: 0.8kg




TA-13
1008140130
Turbine Mini On-Wall Back Box White

Used with:

- TMS Series
- TMIV-1+

Dimensions:

- Size (HxWxD): 122 x 124 x 65mm
- Weight: 0.4kg



TA-32
1008140320
Turbine Mini On-Wall Back Box

Used with:

- TMS+ Series
- TMIV-1+

Dimensions:

- Size (HxWxD): 116.5 x 116.5 x 46mm
- Weight: 0.4kg



TA-33
1008140330
Turbine Extended On-wall Backbox

Used with:

- TEIV+ Series

Dimensions:

- Size (HxWxD): 305 x 120 x 61mm
- Weight: 1.05kg



On Wall Back Box
1008098000
On Wall Back Box for IPVRS-1

Used with:

- IPVRS-1

Dimensions:

- Size (HxWxD): 180 x 92 x 52mm
- Weight: 0.8kg

Flushmount Back Boxes



TA-2
1008140020
US 2-Gang 3 1/2" Deep Back Box

Used with:

- TCIS Series
- TCIV+ Series
- TMS-1
- TMIV-1+

Dimensions:

- Size (HxWxD): 84 x 96 x 90mm
- Weight: 0.5kg



TA-3
1008140030
2 1/2" Deep Flushmount Backbox for Turbine Compact Mini

Used with:

- TMS-1
- TMIV-1+

Dimensions:

- Size (HxWxD): 84 x 96 x 64mm
- Weight: 0.5kg



TA-18
1008140180
Turbine Compact Flush-Mount Back Box

Used with:

- TCIS Series
- TCIV+ Series

Dimensions:

- Size (HxWxD): 231 x 151 x 101mm
- Weight: 1.5kg



TA-34
1008140340
Turbine Extended Flushmount Backbox

Used with:

- TEIV+ Series

Dimensions:

- Size (HxWxD): 308 x 120 x 60mm
- Weight: 0.98kg



Flush Mount Back Box
1008098100
Flush Mount Back Box for IPVRS-1

Used with:

- IPVRS-1

Dimensions:

- Size (HxWxD): 168 x 80 x 50mm
- Weight: 0.8kg



TA-37
1008098300
Flush Mount Back Box for IP Vandal Resistant Substation

Used with:

- VR3G Series

Dimensions:

- Size (HxWxD): 145 x 98 x 66mm
- Weight: 0.8kg



Touchless Sensor
2390020100
Touchless sensor for Turbine Compact stations with Backbox

Used with:

- TCIS Series
- TCIV+ Series

Dimensions:

- Size (HxWxD): 80 x 80 x 28mm
- Weight: 0.2kg



Touchless Sensor Flush Mount
2390020101
Touchless sensor for Turbine Compact stations

Used with:

- TCIS Series
- TCIV+ Series

Dimensions:

- Size (HxWxD): 80 x 80 x 28mm
- Weight: 0.2kg

Miscellaneous




TA-5
1008140050
Bracket for US 2 GANG Double Depth Back Box

Used with:

- TCIS Series
- TCIV+ Series
- TMIS-1
- TMIV-1+

Dimensions:

- Size (HxWxD): 169 x 109 x 10mm
- Weight: 0.2kg



Tamper Switch
1008091010
Tamper Switch for Vandal Resistant Substation TKIE

Used with:

- IPVRS-1



TA-14
1008140140
Microphone windshield for TCIS / TCIV+

Used with:

- TCIS Series
- TCIV+ Series

Dimensions:

- Size (HxWxD): 110 x 15.5 x 12.4mm

Desktop, Control Room & Clean Room Stations



Zenitel Desktop, Control Room & Clean Room Stations

Key Features

- **High-Quality Audio:** Ensures clear and reliable communication.
- **Robust Design:** Built to withstand demanding environments.
- **User-Friendly Interfaces:** Simplifies operation for quick and efficient use.
- **Integration Capabilities:** Seamlessly connects with other communication and security systems.
- **Specialized Features:** Tailored to meet the specific needs of different environments, from noise cancellation in control rooms to antimicrobial surfaces in clean rooms.

ZENITEL CONNECT PRO ICX-AlphaCom IC-EDGE SIP ONVIF

new



ITS-1
1000712
IP Phone with 7" Screen

- 6 lines with up to 6 SIP accounts
- 7" (1024x600) capacitive 10-point touch screen TFT LCD
- H.264 BP/MP/HP and M-JPEG streaming, video resolution up to 720p, frame rate up to 30 fps, bit rate up to 2Mbps
- Full duplex 2-way HD audio with advanced echo cancellation

Dimensions:

- Size (HxWxD): 26.2 x 182 x 122mm
- Weight: 408g



ITSV-4
1490004010
HD IP Video Phone with 5" Screen

- 16 lines with up to 16 SIP accounts
- 5.0" (1280x720) capacitive 5-point touch screen HD TFT LCD
- Built-in 2 mega-pixel CMOS tiltable camera with privacy shutter, 720p 30fps
- 10-way audio conferencing and 3-way video conferencing capability

Dimensions:

- Size (HxWxD): 48 x 243 x 210mm
- Weight: 1kg



ITSV-5
1490005010
HD IP Video Phone with 8" Screen

- 16 lines with up to 16 SIP accounts
- 8" (1280x800) capacitive 10-point touch screen HD IPS LCD
- Built-in 2 mega-pixel CMOS tiltable camera with privacy shutter
- 12-way audio conferencing and 3-way 1080p 30fps video conferencing capability

Dimensions:

- Size (HxWxD): 48 x 263 x 174mm
- Weight: 1.08kg



IPDM-V2
1008400000
IP Desk Master V2

- Large high-contrast display with backlight for excellent readability
- 4 dynamic navigation keys for quick access to system menus and directory entries.
- 10 DAK keys

Dimensions:

- Size (HxWxD): 75 x 168 x 176mm
- Weight: 0.5kg



IPDMH-V2
1008401000
IP Desk Master with Handset V2

- Large high-contrast display with backlight for excellent readability
- 4 dynamic navigation keys for quick access to system menus and directory entries.
- 10 DAK keys

Dimensions:

- Size (HxWxD): 75 x 225 x 176mm
- Weight: 0.7kg



IPDMHB-V2
1008401100
IP Desk Master with Handset (black) V2

- Large high-contrast display with backlight for excellent readability
- 4 dynamic navigation keys for quick access to system menus and directory entries.
- 10 DAK keys

Dimensions:

- Size (HxWxD): 75 x 225 x 176mm
- Weight: 0.7kg



CRM-V-2
1008431000
IP Flush Master Station

- Aluminium front plate
- 4 dynamic navigation keys and 4 DAK keys for quick access to system menus and directory entries.
- White light behind all keys for excellent readability in dark environments

Dimensions:

- Size (HxWxD): 280 x 125 x 30mm
- Weight: 0.63kg



IP-CROR
1008415000
IP Intercom Station for Clean Rooms and Hospital Operating Rooms

- Chemical resistant and anti-bacterial front surface for easy cleaning
- Aluminium front plate
- 4 dynamic navigation keys and 4 DAK keys for quick access to system menus and directory entries.
- Designed to meet the requirements of ISO 14644-1, ISO Designation 5

Dimensions:

- Size (HxWxD): 280 x 125 x 30mm
- Weight: 0.63kg



ECPIR-P
1023200030
Exigo Call Panel, PTT Button

- Indicators for power, call, and fault
- Separate PTT button
- LED Indicators for power, call, and fault
- For single or dual systems (A-B systems)
- Supports up to four **EBMDR-8** expansion modules

Dimensions:

- Size (HxWxD): 144 x 96 x 41.5mm
- Weight: 0.5kg

Desktop, Control Room & Clean Room Stations Accessories

Expansion Modules



ECPIR-3P
1023200033
Exigo Call Panel, Intercom

- Three programmable buttons with individual labels and status indicators
- Indicators for power, call, and fault
- Separate PTT button
- LED Indicators for power, call, and fault
- For single or dual systems (A-B systems)
- Supports up to four **EBMDR-8** expansion modules

Dimensions:

- Size (HxWxD): 144 x 96 x 41.5mm
- Weight: 0.5kg



SDS-1
1490000010
IP SIP Desk Station

- Supports 2 lines, 2 SIP accounts, and 3-way conferencing
- 3 programmable soft keys
- Backlit LCD display
- 2 x RJ45 ports

Dimensions:

- Size (HxWxD): 36.5 x 185 x 186mm
- Weight: 0.73kg



CRM-V-DAK48
1008010100
48-Key DAK Expansion Module for CRM-V-2

- 48 programmable DAK keys
- Visual indications with two LEDs (green/red) per DAK key
- All keys have backlight (adjustable)

Used with:

- CRM-V-2

Dimensions:

- Size (HxWxD): 280 x 125 x 30mm
- Weight: 0.65kg



CRM-V-HS
1008097100
Handset for IP Flush Master CRM-V

- With 1m curly cord

Used with:

- CRM-V-2

Dimensions:

- Size (HxWxD): 280 x 67 x 41mm
- Weight: 0.4kg



EBMDR-8
1023253008
Exigo Button Expansion Module, 8 Buttons

- Eight programmable buttons with individual labels and status indicators
- Optional button protection covers
- LED Indicators for power, call, and fault

Used with:

- ECPIR-P
- ECPIR-3P

Dimensions:

- Size (HxWxD): 144 x 96 x 41.5mm
- Weight: 0.5kg



EAPIR-8
1023201008
 EXIGO Alarm Panel, 8 buttons

- Eight programmable buttons with individual labels and status indicators
- Optional button protection covers
- LED Indicators for power, call, and fault

Used with:

- ECPIR-P
- ECPIR-3P

Dimensions:

- Size (HxWxD): 144 x 96 x 41.5mm
- Weight: 0.5kg

Back Boxes & Mounting Brackets



1490009006
 Wall Mount Bracket for ITSV-4

Used with:

- ITSV-4

Dimensions:

- Size (HxD): 149.2 x 43.5mm
- Weight: 0.1kg



1490009007
 Wall Mount Bracket for ITSV-5

Used with:

- ITSV-5

Dimensions:

- Size (HxWxD): 148 x 135 x 44.7mm
- Weight: 0.1kg



1008091100
 Wall Bracket for Desktop Stations

Used with:

- IPDM-V2
- IPDMH-V2
- IPDMHB-V2

Dimensions:

- Size (HxWxD): 92 x 110 x 46mm
- Weight: 0.2kg



1008098600
 On-wall back box for IP Flush Master Stations

Used with:

- CRM-V-2

Dimensions:

- Size (HxWxD): 280 x 125 x 34mm
- Weight: 0.2kg



1008098700
 Flush Mount Back Box IP Flush Master Stations

Used with:

- CRM-V-2
- CRM-V-DAK48
- IP-CROR

Dimensions:

- Size (HxWxD): 270 x 116 x 40mm
- Weight: 0.5kg



1008098800
 Flush Mount Back Box CRM-V-HS

Used with:

- CRM-V-HS

Dimensions:

- Size (HxWxD): 270 x 58 x 40mm
- Weight: 0.3kg



2810021001
 Wall-mount Backbox for Cleanroom Station

Used with:

- IP-CROR

Dimensions:

- Size (HxWxD): 295 x 140.5 x 65mm
- Weight: 0.9kg



2810020006
 Single Desk Stand for IP Flush Master Stations

Used with:

- CRM-V-2
- CRM-V-DAK48

Dimensions:

- Size (HxWxD): 346 x 155 x 137mm
- Weight: 0.8kg



2810020005
 Dual Desk Stand for CRM-V-2 and Handset

Used with:

- CRM-V-2
- CRM-V-HS

Dimensions:

- Size (HxWxD): 346 x 227 x 137mm
- Weight: 1.3kg



2810020004
Triple Desk Stand for IP Flush Master Stations

Used with:

- CRM-V-2
- CRM-V-DAK48
- CRM-V-HS

Dimensions:

- Size (HxWxD): 346 x 346 x 137mm
- Weight: 1.8kg



EMBR-1
1023595010
Mounting Box for ECPIR, EAPIR and EBM-DR-8 Panels

Used with:

- ECPIR-3P
- ECPIR-P
- EAPIR-8
- EBMDR-8

Dimensions:

- Size (HxWxD): 104 x 188 x 74mm
- Weight: 0.35kg




EMBR-2
1023595020
Mounting Box for ECPIR, EAPIR and EBM-DR-8 Panels

Used with:

- ECPIR-3P
- ECPIR-P
- EAPIR-8
- EBMDR-8

Dimensions:

- Size (HxWxD): 201 x 188 x 74mm
- Weight: 0.7kg



MB-30G
3005020033
Gooseneck Microphone

Used with:

- ECPIR-P
- ECPIR-3P

Dimensions:

- Size (Length): 446mm
- Weight: 0.1kg



PAM1H
1023533012
Handheld Microphone for ECPIR Indoor Access Panels / Intercom Stations

Used with:

- ECPIR-P
- ECPIR-3P

Dimensions:

- Size: Length 142mm, Head Ø 29mm, Body Ø 24mm
- Weight: 0.2kg

Microphones



CRM-V-GN
1008097500
Gooseneck Microphone for IP Flush Master CRM-V-2

Used with:

- CRM-V-2

Dimensions:

- Size (HxWxD): 32 x 90 x 45mm
- Weight: 0.1kg



CRM-VH
2213100000
Headset Solution for IP Flush Master CRM-V-2

Used with:

- CRM-V-2

Dimensions:

- Size (HxWxD): 96 x 96 x 80mm
- Weight: 0.24kg



MDDS
1007007010
Microphone for Dual Display Station

Used with:

- IPDDS

Dimensions:

- Size (Length): 300mm
- Weight: 0.15kg

Miscellaneous



EMBR-6
1023595060
Connection Kit for EMBR-1 and EMBR-2

Used with:

- EMBR-1
- EMBR-2

Dimensions:

- Weight: 0.1kg



Industrial & EX IP Intercom

Industrial Intercom

Key Features

- **Rugged, Heavy-Duty Construction** - Built to withstand most chemical and environmental hazards found on- or offshore, extreme industrial conditions and rough handling.
- **Exceptional audio technology** - high sound pressure level (SPL), automatic volume gain control, and active noise and echo canceling ensures clear communication in noisy industrial settings.
- **Weatherproof & Dustproof** - IP-rated enclosures protect against dust, dirt, water, and extreme temperatures.
- **Hands-Free & PTT (Push-to-Talk) Options** - Enables flexible communication methods based on operational needs.
- **Emergency Call & Alarm Integration** - Can be linked to emergency systems for rapid response in critical situations.
- **Glove-Friendly & Easy-to-Use Interfaces** - Designed for operation in industrial environments, even with protective gear.

ZENITEL CONNECT PRO ICX-AlphaCom IC-EDGE SIP Onvif




TFIE-1
1008122010
Industrial Intercom

- Full keypad with 1 programmable button + keys for manual override (PTT) and Cancel.
- Visible status indicators on front panel

IP66

Dimensions:
• Size (HxWxD): 345 x 118 x 101mm
• Weight: 1.9kg




TFIE-2
1008122020
Industrial Intercom

- 6 programmable, labelled buttons and optional key covers for alarm panel duties.
- Visible status indicators on front panel

IP66

Dimensions:
• Size (HxWxD): 345 x 118 x 101mm
• Weight: 1.9kg



TFIE-6
1008122060
Industrial Intercom

- Full keypad with 4 programmable buttons, keys for manual override (PTT) and Cancel, plus display with scrolling unit
- Visible status indicators on front panel
- PMOLED display

IP66

Dimensions:
• Size (HxWxD): 345 x 118 x 101mm
• Weight: 1.9kg

Ex IP Intercom

Key Features

- **Explosion-Proof** - Designed for use in potentially explosive atmospheres, meeting ATEX Zone 1 and IECEx requirements for safe and reliable operation.
- **Flameproof Design** - Prevents ignition of hazardous substances in the surrounding environment.
- **Rugged, Heavy-Duty Construction** - Built to withstand most chemical and environmental hazards found on- or offshore, extreme industrial conditions and rough handling.
- **Exceptional audio technology** - high sound pressure level (SPL), automatic volume gain control, and active noise and echo canceling ensures clear communication in noisy industrial settings
- **Weatherproof & Dustproof** - IP-rated enclosures protect against dust, dirt, water, and extreme temperatures.
- **Hybrid Support** - Available in both IP and analog versions for flexible integration.

ZENITEL CONNECT PRO ICX-AlphaCom IC-EDGE SIP ONVIF



TFIX-1-V2
1008123110
Ex IP Intercom Station- full keypad

- Full keypad with 1 programmable key
- Visible status indicators on front panel



Dimensions:

- Size (HxWxD): 345 x 178 x 101mm
- Weight: 4kg



TFIX-2-V2
1008123120
Ex IP Intercom Station with 6 buttons

- 6 programmable buttons
- Visible status indicators on front panel



Dimensions:

- Size (HxWxD): 345 x 178 x 101mm
- Weight: 4kg



TFIX-3-V2
1008123130
Ex IP Intercom Station with 3 buttons

- Features 1 oversized call-button and keys for manual override (PTT) and Cancel.
- Visible status indicators on front panel



Dimensions:

- Size (HxWxD): 345 x 178 x 101mm
- Weight: 4kg

Industrial & EX IP Intercom Accessories

Microphones



EMMAI-2H
1023533312
Handheld Compact Industrial Microphone For Exigo/Turbine

Used with:

- TFIE-1
- TFIE-2
- TFIE-6



Dimensions:

- Size (HxWxD): 68 x 44 x 21.5mm
- Cable length: 0,75 m / 2 m (extended)
- Weight: 0.22kg



EMMAX-1H
1023533511
Handheld Industrial EX Microphone For Exigo/Turbine

Used with:

- TFIX-1-V2
- TFIX-2-V2
- TFIX-3-V2



Dimensions:

- Size (HxWxD): 68 x 44 x 21.5mm
- Cable length: 0,75 m / 2 m (extended)
- Weight: 0.22kg

Head- and Handsets



TAX-2B
1008150025
Ex-Approved Plugbox & amp; Cable for Headset with PTT

Used with:

- TFI-1-V2
- TFI-2-V2
- TFI-3-V2
- AK5850HS

IP67

Dimensions:

- Cable length: 10 m



TA-22B
1008140225
Industrial Plugbox & Cable for Headset with PTT

Used with:

- TFI-1
- TFI-2
- TFI-6
- AK5850HS

IP67

Dimensions:

- Cable length: 10 m



AK5850HS

Ex-approved Headset

Used with:

- TFI-1
- TFI-2
- TFI-6
- TAX-2B
- TA-22B
- TFI-1-V2
- TFI-2-V2
- TFI-3-V2

Dimensions:

- Size (HxWxD): 210 x 66 x 70mm
- Weight: 0.4kg



TA-23
1008140230
Industrial Handset for Turbine with PTT

Used with:

- TFI-1
- TFI-2
- TFI-6

IP66

Dimensions:

- Size (HxWxD): 70 x 200 x 50mm
- Cable Length: 1.0 m / 3.5 m (extended)
- Weight: 0.31kg

Power Supply - Flowire Converter

Flowire Converter

Key Features

Flowire, based on the HomePlug AV specification, uses 24-48 V DC and acts as a network bridge between Ethernet and a PLC link.

A single-paired cable distributes both power and data, with longer runs than standard Ethernet, reducing the need for switches or repeaters. Up to nine Flowire devices can connect to the same 2-wire network. Existing infrastructure can be used, lowering retrofit project costs. The Flowire Converter works with any Ethernet-enabled device, not just Zenitel products.

The Flowire Converter enables Ethernet and power to run on the same two wires, simplifying cabling and allowing longer runs.

All Zenitel outdoor intercom stations can use the 2-wire Flowire system to extend Ethernet connections and support power distribution.



FCDC3
1008080310
Flowire Ethernet Converter - DC Voltage

- The cable hauls can be longer, up to 2 km, reducing the need for switches and/or repeaters
- Enable/Disable PoE switch
- **Important!** 24-48V DC non-PoE Ex equipment

Dimensions:

- Size (HxWxD): 74 x 112 x 26mm
- Weight: 0.3kg



Power Supply
2990101120
XP Power Supply, 48Vdc 120W

- Up to 90% Efficiency
- Wide Adjustment Range
- Parallel Function
- DC Standby Versions
- Full Power from -40 °C to +60 °C
- Connector Options

Dimensions:

- Size (HxWxD): 125 x 63.5 x 116mm
- Weight: 0.92kg



Power Supply
2990101240
XP Power Supply, 48Vdc 240W

- Up to 90% Efficiency
- Wide Adjustment Range
- Parallel Function
- DC Standby Versions
- Full Power from -40 °C to +60 °C
- Connector Options

Dimensions:

- Size (HxWxD): 125 x 83 x 111.3mm
- Weight: 1.36kg


Heavy Duty IP Stations



Key Features

- **Exceptional audio performance** - High sound pressure level (SPL), automatic volume gain control, and active noise and echo canceling ensures clear communication in noisy industrial settings
- **Impact-Resistant Construction** - Built 5 mm aluminum casing and stainless steel components to withstand rough handling and heavy industrial use.
- **IP-Rated for Harsh Environments** - Weatherproof and dustproof, ensuring reliable operation in extreme conditions.
- **Analog & Hybrid Options** - Supports both modern and legacy communication systems. Additionally, the heavy-duty stations offer an option for GSM cellular connectivity for increased flexibility in deployment.
- **Push-to-Talk (PTT) & Hands-Free Operation** - Provides flexibility for different use cases.
- **Emergency Call & Alarm Integration** - Can be connected to safety and security systems for rapid response. Supports a wide set of IP and networking standards

ZENITEL CONNECT PRO | ICX-AlphaCom | IC-EDGE | SIP | ONVIF




IPHDT-Y
1008472120
IP Heavy Duty Telephone, Armored 50cm Cord, Yellow

- Hotline telephone, without door

IP66

Dimensions:

- Size (HxWxD): 320 x 205 x 120mm
- Weight: 5kg



IPHDT-DY
1008472220
IP Heavy Duty Telephone, Door, Coiled Rubber Cord, Yellow

- Hotline telephone, with door

IP66 IK10

Dimensions:

- Size (HxWxD): 320 x 205 x 148mm
- Weight: 5.4kg




IPHDT-KY
1008472100
IP Heavy Duty Telephone, Keypad, Armored 50cm Cord, Yellow

- Full keyboard with 3 programmable buttons

IP66

Dimensions:

- Size (HxWxD): 320 x 205 x 120mm
- Weight: 5kg



IPHDT-KDY
1008472200
IP Heavy Duty Telephone, Door, Coiled Rubber Cord, Yellow

- Full keyboard with 3 programmable buttons, with door

IP66 IK10

Dimensions:

- Size (HxWxD): 320 x 205 x 148mm
- Weight: 5.4kg

Public Address & Voice Alarm (PAVA)

Zenitel PAVA combines voice alarm/evacuation and operational public address in a unified system, with supervised audio paths and fault reporting to support dependable operation.

Technical scope

- Public address and paging announcements for operational communication.
- Voice alarm / voice evacuation messaging with prioritised emergency handling.
- Support for emergency microphones and controlled live announcements.
- Zoned messaging and site-wide broadcasts with supervised signal paths.

System Architecture (examples)

- VIPEDIA audio router platform with IP audio capabilities and general-purpose I/O.
- Supports redundant and supervised audio networking and scalable multi-node deployments (clustered systems) with fault reporting.
- Compatible with Zenitel amplifier ranges (e.g., V2000 / V400) as part of the Zenitel PAVA system.

Compliance & integration

- EN 54-16 aligned architectures for regulated installations. Certification depends on project scope and selected components.
- Fire alarm and life-safety interfaces for automated emergency triggering.
- Integration into wider security workflows (e.g., via Zenitel Connect Pro or third-party automation) for operational and security announcements.
- Optional integration with Zenitel Connect Pro (requires Zenitel Connect Pro on ICX-510) to trigger selected PAVA functions from operator workflows (where applicable).

Within this catalogue, only a select few core products are showcased. For our full range, visit zenitel.com/product/safety-security/public-address-voice-alarm-pava-solutions.



VAIA
1200101000

4 Channel Public Address and Voice Alarm Amplifier and Controller

- Comprehensive Controller, Amplification & Battery Charger all-in-one.
- 4+1 channels of power-configurable amplification
- 1U/19", 1000Wrms (total), EN54-16 & EN54-4 system

Dimensions:

- Size (HxWxD): 44 x 436 x 412mm
- Weight: 8kg



INTEGRA-00 - 10

Wall Mount PAVA System (0-10 amp channels pre-installed)

- Self-contained wall mount PAVA System
- Up to 2000W load total
- 24 bit 48kHz audio processing
- 12 analogue audio inputs & outputs / 6 IP audio inputs
- Pre-installed with 3, 5, 7 or 10 amplifier cards
- Interoperable with the Vipedia range

Dimensions:

- Size (HxWxD): 980 x 600 x 220mm
- Weight: 40kg



INTEGRA-PRO-00 - 10

Wall Mount PAVA System (0-10 amp channels pre-installed) - Dante Enabled

- Self-contained wall mount PAVA System
- Up to 2000W load total
- 24 bit 48kHz audio processing
- 12 analogue audio inputs & outputs / 6 IP audio inputs
- Pre-installed with 3, 5, 7 or 10 amplifier cards
- Interoperable with the Vipedia range

Dimensions:

- Size (HxWxD): 980 x 600 x 220mm
- Weight: 40kg



VIPEDIA-12-NET
1200100012

PAVA Audio router with network card

- Fully EN 54-16 certified
- 24 bit 48kHz audio processing
- 12 analogue audio inputs & outputs / 6 IP audio inputs
- Up to 32 units can be grouped together
- Compatible with the V2000 and V400 amplifier ranges

Dimensions:

- Size (HxWxD): 41.8 x 436 x 426mm
- Weight: 3.75kg



VIPEDIA-12-PRO
1200100121

PAVA Audio router with network card - Dante Enabled

- Fully EN 54-16 certified
- 24 bit 48kHz audio processing
- 12 analogue audio inputs & outputs / 6 IP audio inputs
- Up to 32 units can be grouped together
- Compatible with the V2000 and V400 amplifier ranges

Dimensions:

- Size (HxWxD): 41.8 x 436 x 426mm
- Weight: 3.75kg



V2000
1200202000

PAVA 2000W Power Amplifier Mainframe (0 amps pre-installed)

- Up to 2000W in 2U / 19" housing
- EN 54-16 and EN 54-4 compliant
- Houses up to 10 separate amplifier cards
- Hot-swappable amplifiers cards
- Integrated battery charger
- Internal & external standby options

Dimensions:

- Size (HxWxD): 86 x 436 x 425mm
- Weight: 7.7kg



D150
1200202150
PAVA 150W Power Amplifier Module for the V2000 / INTEGRA

- Fully EN 54-16 certified
- Class D transformerless amplifiers
- 100V, 70V or 50V output
- Compatible with the V2000 mainframe and Integra range Pre-installed with 3, 5, 7 or 10 amplifier cards

Dimensions:
• Weight: 0.8kg



D500
1200202500
PAVA 500W Power Amplifier Module for the V2000 / INTEGRA

- Fully EN 54-16 certified
- Class D transformerless amplifiers
- 100V, 70V or 50V output
- Compatible with the V2000 mainframe and Integra range Pre-installed with 3, 5, 7 or 10 amplifier cards

Dimensions:
• Weight: 0.8kg



LSZDC
1200540000
PAVA Amplifier Interface Module for the V2000 / INTEGRA

- EN 52-16 certified amplifier interface card
- Powerful on-board DSP capability
- DC / impedance / loop monitoring (A to B)
- Independently monitored A / B line output fed from a single amplifier
- Compatible with the V2000 mainframe and Integra range

Dimensions:
• Weight: 0.8kg

SIP Amplifiers

Key Features

- **Superior Audio Performance** - High-power output, wide frequency response, and low-latency audio processing ensure strong, clear sound for effective communication, even in large or noisy environments.
- **SIP & IP-Based Connectivity** - Easily integrates with VoIP systems, intercoms, and PAVA solutions.
- **Multicast & Unicast Support** - Enables efficient audio distribution across large sites.
- **Industrial-Grade Build** - Designed for reliable operation in harsh environments.
- **Failover & Redundancy Support** - Ensures continuous operation, even in case of network issues.

SIP



VIPA-WS
1200450150
Public Address Touch Screen Workstation

- Versatile and intuitive public address control and supervision front end
- Supports up to 384 PAVA zones
- Live paging
- PAVA system audio monitoring and supervision
- Message management, recording, playback and scheduling



EMS01 - EMS50
Wall Mount Emergency Mic

- Equipped with single PTT and up to 50 physical buttons
- EN 54-16 compliant indicators and controls
- Live, store +forward & recorded broadcasts
- Built-in loudspeaker with listen-in function

IP65

Dimensions:
• Size (HxWxD): 402.5 x 344 x 95mm
• Weight: 6kg



MPS01-G - MPS50-G
Desk Mount Paging and Emergency Mic with PTT - Gooseneck - IP enabled

- Equipped with single PTT and up to 50 physical buttons
- EN 54-16 compliant indicators and controls
- Live, store +forward & recorded broadcasts
- Built-in loudspeaker with listen-in function
- Wall mount and fist microphone

Dimensions:
• Size (HxWxD): 58 x 175 x 200mm
• Weight: 1kg



ENA2100-AC2
1023102110
Exigo Network Amplifier 2 x 100W AC

- 2x 100 watt continuous GA power

Dimensions:
• Size (HxWxD): 87 x 482 x 372mm
• Weight: 10.7kg



ENA2200-AC2
1023102210
Exigo Network Amplifier 2 x 200W AC

- 2x 200 watt continuous GA power

Dimensions:
• Size (HxWxD): 87 x 482 x 372mm
• Weight: 11.2kg



ENA2060-DC1
1023122061
Exigo Network Amplifier with 2 60 W Amplifier Channels 110 V DC

- 2x 60 watt
- Fan-less
- 2 SIP addressable channels

Dimensions:
• Size (HxWxD): 87 x 482 x 372mm
• Weight: 11.2kg

PAVA Accessories



BMB02
1200550031
Din Rail Mount I/O Expansion Device

- Low profile DIN rail mount casing
- Expands the capability of the audio router
- 12 analogue inputs
- 12 digital (opto-isolated) inputs
- 12 digital (open collector) outputs
- Up to 9 units can be connected in parallel

Used with:

- VIPEDIA-12 Range
- INTEGRA Range

Dimensions:

- Size (HxWxD): 92 x 159 x 44mm
- Weight: 0.37kg



RAK-DUCT-01
1200571000
Cooling Duct 1U for the V2000

- Optimum V2000 cooling
- Standard 19" rack installations

Used with:

- VIPEDIA-V2000 Range
- RAK-FAN-01

Dimensions:

- Size (HxWxD): 44.4 x 483 x 263.6mm
- Weight: 1.3kg



RAK-FAN-01
1200542001
Fan Shelf 1U for the V2000

- Optimum V2000 cooling
- Standard 19" rack installations

Used with:

- VIPEDIA-V2000 Range
- RAK-DUCT-01

Dimensions:

- Size (HxWxD): 44.4 x 483 x 263.6mm
- Weight: 2.4kg



VIPEDIA-BOA01
1200550010
Din Rail Mount RJ45 Breakout Adapter - Single Port

- DIN rail mounted
- Break out of all of the connections from one RJ45 port, to eight screw terminals plus screen terminals
- End of line monitoring resistor positions
- Additional dual redundant power inputs and output power terminals
- Additional screen connection and output cable screen terminals

Used with:

- VIPEDIA Range

Dimensions:

- Size (HxWxD): 33 x 88 x 52mm
- Weight: 0.1kg



ANS04-ES
1200500040
Wall Mount Sample and Hold Ambient Noise Sensor

- Sample and hold noise sensor
- Extended temperature range
- Fail safe operation



DANS01
1200500010
Wall Mount Dynamic Ambient Noise Sensor

- Dynamic noise sensor
- Extended temperature range
- Fail safe operation



MPX10
1200571067
Expansion Module for MPS01 with 10 buttons


- Easy to install expansion module with fittings
- Add additional 10 physical buttons

Used with:

- MPS range of microphones

Dimensions:

- Size (HxWxD): 58 x 285 x 200mm
- Weight: 1.2kg



VIPEDIA-BOA02
1200550020
Din Rail Mount RJ45 Breakout Adapter - Four Port

- DIN rail mounted
- Break out of all of the connections from four RJ45 ports, each to eight screw terminals plus an output cable screen terminal

Used with:

- VIPEDIA Range

Dimensions:

- Size (HxWxD): 35 x 61 x 117mm
- Weight: 0.1kg



BDU01
1200550033
PAVA Beacon Driver Unit

- DIN rail mounted
- 6 individually fused outputs 18-69 VDC

Used with:

- VIPEDIA Range
- INTEGRA Range
- V2000-POK01

Dimensions:

- Size (HxWxD): 40 x 251 x 102mm
- Weight: 1.07kg



V2000-POK01
1200550032
Power Output Card Kit for V2000 or INTEGRA Frame

- Provides access to spare battery capacity in the V2000 or Integra frame
- Offers a fused DC output up to 9A @ 24 VDC
- 2 Separate Cards

Used with:

- VIPEDIA-V2000 Range
- INTEGRA Range
- BDU01

Dimensions:

- Size (HxWxD): Rear Card: 50 x 15 x 130mm, Front Card: 80 x 20 x 275mm
- Weight: Rear: 0.36kg, Front: 0.115kg

IP65

Used with:

- VIPEDIA-12 Range
- INTEGRA Range

Dimensions:

- Size (HxWxD): 160 x 100 x 81mm
- Weight: 0.98kg

IP65

Used with:

- VIPEDIA-12 Range
- INTEGRA Range

Dimensions:

- Size (HxWxD): 160 x 100 x 81mm
- Weight: 0.98kg

IP Speakers

Zenitel's IP Speakers with microphone

Key Features

- **Zenitel Audio Presence** - High with sound pressure level (SPL), wide frequency response, and advanced audio processing ensure crystal-clear audio in any setting.
- **IP-Based Connectivity** - Easily integrates into existing IP networks, enabling centralised control and monitoring.
- **Built-in Microphone** - Supports half-duplex (Push-to-Talk) audio for clear and reliable two-way communication.
- **Multicast & Unicast Support** - Supports efficient audio distribution across large sites or multiple zones.
- **Power over Ethernet (PoE)** - Simplifies installation by reducing the need for additional power sources.

ZENITEL CONNECT PRO ICX-AlphaCom IC-EDGE SIP ONVIF



ZIPS-H
1023321311
Zenitel IP Speaker - Horn

- 120 dB Max Sound Pressure Level 1kHz/1m
- 275 - 7000 Hz Frequency range

IP66 IK08

Dimensions:

- Size (HxWxD): 152 x 253 x 309mm
- Weight: 1.85kg



ZIPS-HHO
1023321330
Zenitel IP Speaker - Horn High Output

- 123 dB Max Sound Pressure Level 1kHz/1m
- 240 - 10000 Hz Frequency range

IP66 IK08

Dimensions:

- Size (HxWxD): 170 x 315 x 350mm
- Weight: 2.49kg



ZIPS-C
1023320011
Zenitel IP ceiling speaker

- 105 dB Max Sound Pressure Level 1kHz/1m
- 250 - 10000 Hz Frequency range
- Steel fire dome

Dimensions:

- Size (Diameter x Depth): 199 x 146mm
- Weight: 1.2kg



ZIPS-WC
1023322330
Zenitel IP Speaker - Wallmount Cabinet

- 103 dB Max Sound Pressure Level 1kHz/1m
- 90 - 20000Hz (± 20%) Frequency range

IP66

Dimensions:

- Size (HxWxD): 160 x 255 x 189mm
- Weight: 2.1kg

IP Station Kits

Zenitel's IP Station Kits provide a comprehensive communication solution, designed for quick installation and seamless integration into existing IP networks. Ideal for intercom systems, entry points, public address, and security applications across various industries, these kits offer robust functionality and deliver the superior audio quality that Zenitel intercoms are known for.

Key Features

- **Exceptional audio technology** - High sound pressure level (SPL), automatic volume gain control, and active noise and echo canceling ensures clear communication in noisy industrial settings.
- **Pre-Configured for Easy Deployment** - Ready to be connected to your network with minimal configuration required.
- **Flexible Communication Options** - Supports full open duplex provides free-flowing hands-free communication or push-to-talk (PTT) communication, depending on your operational needs.
- **IP-Based Connectivity** - Easily integrates into existing IP networks, enabling remote management and monitoring.
- **Cybersecurity Hardened** - Designed with built-in security features to prevent unauthorized access and protect communication.

ZENITEL CONNECT PRO ICX-AlphaCom IC-EDGE SIP ONVIF



ZMK-1
1008560101
Zenitel Multipurpose Kit

- Dual RJ45 for PoE and Ethernet connectivity (with switch)
- 2 configurable inputs and outputs to activate door openers and sensors
- High quality and high power 15W audio amplifier
- Wide selection of open standard connectors and interfaces such as USB, HDMI, and dry contacts

Dimensions:

- Size (HxWxD): 36.5x 154 x 71.4mm
- Weight: 0.32kg



TKIE-1
1008132010
Turbine Extended IP Kit

- Dual RJ45 for PoE and Ethernet connectivity (with switch)
- Dual relays (DPDT)
- Possibility for connecting high-power relay module (TA-10)

Dimensions:

- Size (HxWxD): 65 x 100 x 25mm
- Weight: 0.1kg



TKIE-2
1008132020
Turbine Extended IP Kit

- Dual RJ45 for PoE and Ethernet connectivity (with switch)
- Dual relays (DPDT)
- Possibility for connecting high-power relay module (TA-10)

Dimensions:

- Size (HxWxD): 74 x 106 x 30mm
- Weight: 0.1kg



TKIE-3CC
1008132035
Turbine Extended IP Kit with Keyscan

- 5x5 key-scan matrix
- Dual RJ45 for PoE and Ethernet connectivity (with switch)
- Dual relays (DPDT)
- Possibility for connecting high-power relay module (TA-10)
- Conformal coating

Dimensions:

- Size (HxWxD): 65 x 100 x 25mm
- Weight: 0.1kg



TKIV+
1008331010
Turbine Video - VoIP Intercom Module

- HD video up to 1080p resolution
- Wide angle lens with 180 degrees field of view horizontally and vertically
- High performance hardware platform with 4 x Cortex-A53 CPU cores and 512MB LPDDR4 RAM

Dimensions:

- CPU Size (HxWxD): 89 x 108 x 31mm
- Video module Size (HxWxD): 89 x 66 x 31mm



TKIS-1
1008131010
Turbine Kit IP Standard

- Standard IP Kit with Zenitel's audio technology and support of a wide set of IP and networking standards

Dimensions:

- Size (HxWxD): 65 x 100 x 25mm
- Weight: 0.1kg



TKIS-1CC
1008131015
TKIS-1, Conformal coated

- Standard IP Kit with Zenitel's audio technology and support of a wide set of IP and networking standards
- Conformal coating

Dimensions:

- Size (HxWxD): 65 x 100 x 25mm
- Weight: 0.1kg



IPMSK-V2
1008493000
IP Master Station Kit PCB-V2

- Dual RJ45 for PoE and Ethernet connectivity (with switch)
- Supports external audio amplifier

Dimensions:

- Size (HxWxD): 88 x 151.5 x 20mm
- Weight: 0.25kg



TKIS-2
1008131020
Audio Intercom Kit

- DIN-rail mountable, clips included

Dimensions:

- Size (HxWxD): 32 x 117 x 71mm
- Weight: 0.1kg



TKIS-2CC
1008131025
TKIS-2, Conformal coated

- DIN-rail mountable, clips included
- Conformal coating

Dimensions:

- Size (HxWxD): 32 x 117 x 71mm
- Weight: 0.1kg

IP Station Kit Accessories



IP-LCM-A
1008095201
IP Line Expansion Module with Inputs/Outputs

- 8 relay outputs
- 8 control inputs
- Robust push-in connectors for cables up to 1.5 mm² / 16 AWG
- Audio in/out for interfacing to other systems

Used with:

- TKIS-2

Dimensions:

- Size (HxWxD): 125.4 x 270.5 x 66.6mm



TA-10
1008140100
Relay Module

- Dual high-power relays (DPDT)
- Up to 400VAC / 48 VDC per relay
- Up to 6A current per relay
- Heavy-duty spring-loaded terminals with spare grounding terminals

Used with:

- TKIE-1
- TFIE Series

Dimensions:

- Size (HxWxD): 50 x 100 x 40mm
- Weight: 0.1kg



TA-16
1008140160
Loudspeaker

- 5 speakers included
- Maximum power: 8 W
- Nominal impedance Z: 8 Ω
- Frequency range: 120–20000 Hz
- SPL peak power: 86 dB

IP65

Used with:

- TKIE-2
- TKIS-2

Dimensions:

- Size (HxWxD): 68 x 68 x 31mm
- Weight: 0.05kg



TA-17
1008140170
Electret Microphone

- 10 microphones included

Used with:

- TKIE-2
- TKIS-2

Dimensions:

- Cable length: 120mm

Zenitel Connect Pro

Unified Critical Communication Platform

Zenitel Connect Pro is a software-driven unified critical communication platform that consolidates intercom, IP speakers, public address, voice alarm and general alarm systems into one system. It is designed to complement security ecosystems (e.g., VMS and access control) with unified operator workflows across sites.

Deployment & Management

- Deployment options: dedicated ICX-510 server or OVA images for VMware.
- Web-based management: configure and operate system, devices, users, and features via Zenitel Connect Web.
- Scales from single sites to multi-site estates through modular, software-centric architecture.

Media & Operator Workflows

- Native support for audio and video communications.
- Supports unified operator workflows that combine audio actions with security events and visual verification.

Integration & Automation

- Open standards (device support): SIP and ONVIF.
- Zenitel Link integration interfaces: REST API + PubSub (real-time events and control), documented via OpenAPI (Swagger).
- PubSub enables event monitoring such as device online/offline, conversation state (idle/ringing/in conversation), and device I/O state changes.
- Automation: native Node-RED support for custom workflows and site logic (security and operational use cases).
- Note: Zenitel Link integrations require ZCL-API integration license (incl. ONVIF via Zenitel Link).

Cloud Connectivity (Optional)

- Cloud Connection can be enabled in Zenitel Connect Web to support cloud-assisted monitoring and remote management.
- Requires a Zenitel cloud account.

Cybersecurity & Hardening (high level)

- Cybersecurity is a core design criterion; requests are authorized and authenticated.
- Supports certificate handling for trusted web/server operation and secure connectivity.
- Encryption support for communications to devices and external interfaces is available in Zenitel Connect Pro software releases.

Service & Diagnostics (capability examples)

- Extended system and device monitoring capabilities include initiating tone test and button test (software feature).
- Improved logging and reporting capabilities (including syslog support) are available in software releases.

Optional Integrations

- Vikipedia PAVA integration is available to trigger functions within Vikipedia PAVA from Zenitel Connect Pro (configuration required).



Cloud Device Monitoring & Management



ICX-510
1002000200
Server platform for Zenitel Connect Pro

- Capacity: supports up to 50 concurrent calls and up to 200 IP devices per server.
- Robustness: dual software images to reduce downtime during upgrades.
- Security: secure boot and hardware Root of Trust.
- Networking: 2 x 1GbE interfaces.
- Form factor: compact 1U fanless, vibration-proof design; wall or 19" rack mounting.
- Power: low-power footprint (max 15 W).
- Expandability: storage expansion via MicroSD/USB.

ICX-510 is Zenitel's dedicated, hardened server platform for Zenitel Connect Pro, providing the on-premises compute foundation for unified critical communications with HD voice and video support. It is designed for high uptime in demanding operational environments and supports secure operation through built-in hardware security features and hardened platform services.

- Dimensions:**
- Size (HxWxD): 44.5x162 x 200mm
 - Weight: 1kg

Zenitel Connect Pro Licenses



ZCL-IC1
1002700101
Devices

- Each IP device connected to Zenitel Connect Pro requires this license. The maximum number of devices supported is 200.

ZCL-API
1002720900
Integration

- License for integration. This is an on/off license, so only one needed.

ZCL-PBX
1002720100
SIP Trunk

- License required for communicating with 3rd party IPBX and Call Managers. One per defined trunk.

ZCC_x64
1002700000
Zenitel Connect Pro Core

- License to run Zenitel Connect Pro in a supported x64 virtual environment.

ZCUL-IC
1002790001
Software Maintenance Subscription


- Upgrade subscription, per device - 3 years.

ZCL-IVAA
1002729100
Audio Analytics

- Intellivision Audio Analytics License. One license per device.



new



ZC-RMM
1015909

Zenitel Cloud Remote Monitoring & Management

- Unified real-time dashboard with customisable widgets for health and trends.
- Quick onboarding via Zenitel Connect Pro using Device Cloud ID claiming.
- Multi-customer separation with tenant/customer and Space scoping plus granular role-based access.
- Operational workflows to cut downtime: guided claiming, maintenance windows, bulk actions, and history-preserving like-for-like replacement.

Claiming Model

- Each device/system can be claimed by one organisation and located in a single Space; moving between Spaces is allowed.
- Claiming is typically done per Zenitel Connect Pro system; connected endpoints are registered and presented as child devices.
- Moving a device to another customer requires deleting device history and re-claiming.

Requirements

- Zenitel Connect Pro configured for Zenitel Cloud connection. Enable Cloud Connection in Connect Web and sign in with a Zenitel Cloud account.

Optional Subscription Capabilities

Subscription can enable remote configuration, firmware management and extended diagnostics.

Security

Authenticated, encrypted communications with tenant/Space scoping and role-based, least-privilege access.

Licensing / Ordering

Annual subscription per device. No physical product. Available through Zenitel's partner channel.

ICX-510 Accessories

Mounting Brackets



IA-MB1
1002500020
Mounting Bracket for ICX-510/ICX-510-IA

Used with:

- ICX-510
- ICX-510-IA

Dimensions:

- Size (HxWxD): 28 x 169 x 202mm
- Weight: 0.4kg



IA-RS1
1002500010
Mounting Bracket for ICX-510/ICX-510-IA
-19"

Used with:

- ICX-510
- ICX-510-IA

Dimensions:

- Size (HxWxD): 44 x 483 x 203mm
- Weight: 0.4kg

Power Supply



IPS-AC1
1002510000
PSU for ICX-510/ICX-510-IA

Used with:

- ICX-510
- ICX-510-IA

Dimensions:

- Size (HxWxD): 90 x 35 x 55mm
- Weight: 0.12kg

FXS Gateway



FXS-GW-24P
2200001003
FXS Gateway, 24 ports, 100-240VAC

Used with:

- ICX-510-IA

Dimensions:

- Size (HxWxD): 44 x 440 x 185mm
- Weight: 2.63kg

ICX-AlphaCom



ICX-AlphaCom - Intelligent Communication Gateway

ICX-AlphaCom is a comprehensive platform designed for integrated security communication over IP. It unifies various communication systems such as intercoms, radios, public address (PA), and telephony, and integrates these with security components like fire alarms, access control, and CCTV systems. This integration provides a streamlined and efficient communication network crucial for security and operational efficiency in various environments.

ICX-AlphaCom is a robust, scalable, and versatile solution that meets the complex communication and security needs of modern infrastructures, ensuring efficient and secure operations across different sectors.



ICX-510-IA
1002000110
 ICX-510 incl ICX-AlphaCom Core

- Supports up to 552 IC devices per node
- State-of-the-art quad-core processing capacity
- Dual software images for system robustness and low downtime during software upgrades
- Native API & cloud connectivity
- High speed network ports to support multiple calls
- Large memory supports future feature expansion and new services

Dimensions:

- Size (HxWxD): 44.5x162 x 200mm
- Weight: 1kg

For accessories please see **ICX-510 Accessories**

ICX-AlphaCom Licenses



These are the licenses for running ICX-AlphaCom Core on the ICX-510-IA Intelligent Communication Gateway. All licenses can be stacked.

<p>ICX-Core_x64 1002600000 ICX-AlphaCom Core_x64</p>	<ul style="list-style-type: none"> • ICX-AlphaCom Core for x64
<p>ILS-IC 1002600100 IP Station License</p>	<ul style="list-style-type: none"> • Device license
<p>ILS-CRM 1002600200 IP-station license, CRM</p>	<ul style="list-style-type: none"> • CRM license, enables the use of DAK48 module
<p>ILS-SC 1002600300 IP Station License, SoftClient</p>	<ul style="list-style-type: none"> • Device license for SoftClient • The SoftClient will turn a PC into a Zenitel Intercom, providing access to a wide set of critical communication services.
<p>ILS-ARIO 1002600400 IP-ARIO Audio License - 1 IP-ARIO</p>	<ul style="list-style-type: none"> • The IP-ARIO is a multi-purpose unit providing I/O and audio interfaces to radio and PA amplifiers. The audio feature requires an ILS-ARIO license, one for each IP-ARIO unit.
<p>ILS-AMP 1002600500 Exigo amplifier channel license</p>	<ul style="list-style-type: none"> • The ENA Amplifier Channel License allows you to connect an ENA Network Amplifier to ICX-AlphaCom over IP.



ILS-AVC
1002600600
Exigo AVC license

ILS-SIP
1002600700
SIP Station License

- Device license for connecting to 3rd party devices

ILI-AN2
1002602001
AlphaNet License

- AlphaNet, 2 lines
- The AlphaNet license makes it possible to establish communication between ICX-AlphaCom, AlphaCom E and AlphaCom XE nodes in an IP network

ILI-AN8
1002602003
AlphaNet License

- AlphaNet, 8 lines
- The AlphaNet license makes it possible to establish communication between ICX-AlphaCom, AlphaCom E and AlphaCom XE nodes in an IP network

ILI-SIP2
1002602101
SIP Trunking License

- SIP Trunking, 2 lines
- The SIP Trunking License is required to establish a SIP-trunk between ICX-AlphaCom and a 3rd party SIP-server

ILI-SIP4
1002602102
SIP Trunking License

- SIP Trunking, 4 lines
- The SIP Trunking License is required to establish a SIP-trunk between ICX-AlphaCom and a 3rd party SIP-serve

ILI-SIP8
1002602103
SIP Trunking License

- SIP Trunking, 8 lines
- The SIP Trunking License is required to establish a SIP-trunk between ICX-AlphaCom and a 3rd party SIP-serve

ILI-REC2
1002602201
Active Recording Interface License

- Active Recording Interface, 2 Users
- Allows for a SIP call session to be recorded recorded ro a compatible Network Audio Recorder.

ILI-REC8
1002602203
Active Recording Interface License

- Active Recording Interface, 8 Users
- Allows for a SIP call session to be recorded recorded ro a compatible Network Audio Recorder.

ILI-REC16
1002602204
Active Recording Interface License

- Active Recording Interface, 16 Users
- Allows for a SIP call session to be recorded recorded ro a compatible Network Audio Recorder.

ILI-REC32
1002602205
Active Recording Interface License

- Active Recording Interface, 32 Users
- Allows for a SIP call session to be recorded recorded ro a compatible Network Audio Recorder.

ILI-API64
1002602306
API License

- API License supporting 64 Stations

ILI-API512
1002602309
API License

- API License supporting 512 Stations



ILI-IF
1002602400
Interface Enabling License

- Enables the ACDP, MPC, EDO/EDI and ESPA444 interfaces.
- This license is not needed if the API license is present.

ILF-M-BAS
1002604000
Audio Messaging License

- The license have the capacity to both store and play audio messages.
- Max 10 Mbyte used for the above mentioned custom audio messages

ILF-M-ENH
1002604100
Audio Messaging License

- The license have the capacity to both store and play audio messages.
- Max 50 Mbyte used for the custom uploadable audio messages.

ILF-M-EXT
1002604200
Audio Messaging License

- The license have the capacity to both store and play audio messages.
- Possibility to store messages on SD-card or USB-stick for increased storage space

ILF-HBA
1002604500
High bandwidth audio license

- The HD Audio license allows for high bandwidth audio streaming to distribute background music.

ILR-U64
1002606006
Redundancy License 64 Users

ILR-U256
1002606008
Redundancy License 256 Users

ILR-U512
1002606009
Redundancy License 512 Users

ICX-AlphaCom Application Software

AlphaPro

AlphaPro is the tool for configuring the ICX-AlphaCom system. It is self-contained, simple to install and easy to use. When a new server is to be configured, the server is given a working default factory setting.

The operator can then modify the settings such as:

- Directory (type of station, line interface, display name and more)
- Define groups (cell groups, guard groups)
- Interface to CCTV, PA, Paging, DECT
- AlphaNet
- Other custom behavior

There are currently over 100 defined features that can be programmed with AlphaPro. As AlphaPro is an off-line tool, it is possible to enter all parameters without being connected to the server. Once all parameters are entered, AlphaPro can be connected to the server and the parameters can be sent. AlphaPro can also upload configuration information from a server.

- AlphaPro connects to a server via the IP network AlphaPro E7 runs without a hardware key. It gives access to all features except AlphaNet, but only for 36 subscribers.

AlphaPro Professional uses the Professional hardware key. It provides access to all features for all stations. This version must be used when extensive changes to the autoloader are required.



AlphaPro Professional
1009291120
USB Dongle

Vingtor-Stentofon Operator

Vingtor-Stentofon Operator is a PC-based system management application package for the ICX-AlphaCom platform. It shows the status of intercom devices by way of maps and makes it easy for operators to:

- View calls and call requests
- Act easily and quickly on events and requests
- Store an on-screen history of events through a Journal

The application is primarily intended for use in a control room environment. It provides a clear overview for operators with multiple layout possibilities according to the operator's preference. Layouts can be defined to cover single or multiple screens and can be added, edited and deleted by administrators.

Audio Messaging

With Audio Messaging you can store and play audio messages directly from your PC or intercom station, and the messages are safely stored in the flash memory of the ICX-AlphaCom system. Audio Messaging supports a wide set of applications including auto-attendant, PA broadcasting, voice response and voice driven menus. It is easy to initiate audio messages from 3rd party systems using OPC, SDK or Data Protocol. Make live PA and group call broadcasts with recall for handling feedback and verifying messages. Schedule PA and group broadcasts for specific events and set up an auto-attendant with voice guided menus for handling incoming calls. You can also set up a voice response for call request waiting messages and absence messages.

VS-Operator
1191101000
Vingtor-Stentofon Operator Basic License

VS-Operator
1191101010
Vingtor-Stentofon Operator Enhanced License

Software Development Kit

The Software Development Kit (SDK) makes it easy for 3rd-party developers to make value-added applications for integration with the ICX-AlphaCom system. The SDK is based on Microsoft .NET technology. This gives the 3rd-party developer access to a wide set of software components as well as an extensive Microsoft .NET development environment and tool set. Some examples of applications that can be made using the SDK:

- Integrated control room panel on a touch-screen for public address, radio and intercom
- Interactive intercom icons on a map with ability to call, broadcast public address, and listen in
- Integration with video analytics to provide voice response if someone is trespassing
- Integration with CCTV, where a camera is switched on with Voice Activity Detection
- PC-based Call Handler with graphical user interface for control rooms and guards

The SDK consists of a number of assemblies (DLLs) that can be easily integrated with software written in C#.

To further support 3rd-party developers, help files, a quick start manual, Wiki pages and example applications including source code are available to get you quickly up to speed with writing value-added applications for the ICX-AlphaCom system.

To get access to the SDK, please visit: www.zenitel.com/sdk-alphacom

OPC

OPC provides easy and fast integration based on standard OPC technology. OPC is licensed by the ILI-API64 and ILI-API512 licenses.

The ICX-AlphaCom OPC Server implements the following OPC standards:

- OPC Data Access (OPC DA V2/V3)
- OPC Alarm & Events (OPC AE V1.1)
- OPC Unified Architecture (OPC UA)

VS Recorder

- ICX-AlphaCom Call Recording
- Audio and Video Stream Recording

The VS Recorder software is a fully-featured IP based audio recorder with additional support for video recording. The solution is able to record calls from all types of terminals connected to ICX-AlphaCom: IP intercoms and IP phones. The Recorder is also a NAVR – Network Audio/Video Recorder.

VS-Recorder
1190110100
VS Recorder Software - Base Module

VS-Recorder
1190110110
VS Recorder Software - Playback/ Configuration Client

VS-Recorder
1190110120
VS Recorder Software - AlphaCom Recording Module

VS-Recorder
1190110121
VS Recorder Software - AlphaCom Recording Module, AddOn

VS-Recorder
1190110131
VS Recorder Software - Stream Recording Module, 1 stream

VS-Recorder
1190110138
VS Recorder Software - Stream Recording Module, 8 streams

VS-Recorder
1190110160
VS Recorder Software - API

VS-Recorder
1190110180
VS Recorder Software - Secure Audio Export

IC-EDGE Licenses

IC-EDGE uses a simple and scalable licensing model. The system supports up to 32 Zenitel IP stations without any software license and can be expanded with additional station licenses to a total of 64 Zenitel IP stations. Separate licenses are available for third-party SIP devices and telephone gateways, with support for up to 10 of each. The license key is linked to the MAC address of the Edge Controller.



IC-EDGE Station License
1009661001
 1 x IC-EDGE-IP Station License

IC-EDGE Station License
1009661006
 6 x IC-EDGE-IP Station License

IC-EDGE SIP
1009661201
 1 x IC-EDGE-SIP-Client Extensions

IC-EDGE SIP
1009661206
 6 x IC-EDGE-SIP-Client Extensions

IC-EDGE TelTrunk
1009662001
 IC-EDGE TelTrunk



Learn more
about Zenitel
products and
solutions

